




Connectors > Automotive Connectors > Automotive Housings > LEAVYSEAL Connector Housings



Connector System: **Wire-to-Wire**
Number of Positions: **62**
Connector & Housing Type: **Housing for Male Terminals**
Centerline (Pitch): **4 mm, 5 mm [.157 in, .197 in]**
Sealable: **Yes**

[All LEAVYSEAL Connector Housings \(64\)](#)

Features

Product Type Features

Mixed & Hybrid Connector	Yes
Connector Shape	Rectangular
Connector System	Wire-to-Wire
Connector & Housing Type	Housing for Male Terminals
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable
Primary Locking Feature	On the Terminal

Configuration Features

Number of Positions	62
Number of Rows	3, 4

Electrical Characteristics

Operating Voltage	36 VDC
-------------------	--------



Body Features

Cable Exit Angle	90°
Primary Product Color	Gray
Connector & Keying Code	B

Contact Features

Contact Size	1.6mm, 2.8mm
Contact Type	Tab
Mating Tab Width	1.6 mm, 2.8 mm [.063 in] [.11 in]
Contact Current Rating (Max)	10 A, 30 A

Mechanical Attachment

Terminal Position Assurance	Yes
Strain Relief	With
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Panel Mount

Housing Features

Housing Material	PBT GF20
Centerline (Pitch)	4 mm, 5 mm [.157 in] [.197 in]

Dimensions

Connector Height	45.8 mm [1.803 in]
Product Width	70.7 mm [2.783 in]
Product Length	113.25 mm [4.459 in]
Row-to-Row Spacing	1.5 mm [.059 in]

Usage Conditions

Operating Temperature (Max)	120 °C [248 °F]
Operating Temperature Range	-40 – 120 °C [-40 – 248 °F]

Operation/Application

Circuit Application	Power
---------------------	-------

Industry Standards

Degree of Protection	IP67, IP69K
UL Flammability Rating	UL 94HB

Packaging Features



Packaging Quantity	80
Packaging Method	Box

Other

Serviceable	Yes
Connector Position Assurance Capable	No

Product Compliance

For compliance documentation, visit the product page on TE.com>


EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts





TE Part # CAT-L489-CH8172
LEAVYSEAL Connector Housings



TE Part # CAT-L489-B128
LEAVYSEAL Connector Backshells



TE Part # CAT-L489-M8649
LEAVYSEAL Mounting Accessories



TE Part # 964972-1
EINZELLEITERDICHTNG



TE Part # 828905-1
SINGLE-WIRE-SEAL(5MM HOLE)



TE Part # CAT-T4827-T273
TIMER, RECEPTACLE AND TAB



TE Part # 2-2293551-1
62POS,MIXED,REC HSG,ASSY,SLD




TE Part # 8-1579018-1
INSERTION TOOL




TE Part # 2-964269-2
TAB A 1.6x0.6 CONTACT CF SWS Ag

TE Part # 1718329-3
ADAPTER FOR TAB HSG 39 POS,62P


Also in the Series | LEAVYSEAL




Automotive Connector Caps & Covers
(18)



Automotive Housings(79)



Insertion & Extraction Tools(5)




Other Automotive Connector
Accessories(15)



PCB Headers & Receptacles(16)

Customers Also Bought



Documents

Product Drawings
1.5/2.8MM TAB HSG.,62POS.,SEALED
English

CAD Files
3D PDF
3D
Customer View Model
ENG_CVM_CVM_2-1718324-1_D1.2d_dxf.zip
English
Customer View Model
ENG_CVM_CVM_2-1718324-1_D1.3d_igs.zip
English
Customer View Model
ENG_CVM_CVM_2-1718324-1_D1.3d_stp.zip
English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages
ICT Terminals and Connectors Catalogue
English

Product Specifications
Application Specification
English
Application Specification
German

2-1718324-1

Housing for Male Terminals, Wire-to-Wire, 62 Position, 4 mm / 5 mm [.157 in / .197 in]
Centerline, Sealable, Gray, Wire & Cable, Power, LEAVYSEAL

