


Metal Film Resistors

General Type

Normal & Miniature Style [MFR Series]



INTRODUCTION


The MFR Series Metal Film Resistors are manufactured using a vacuum sputtering system to deposit multiple layers of mixed metal alloys and passivative materials onto a carefully treated high grade ceramic substrate. After a helical groove has been cut in the resistive layer, tinned connecting leads of electrolytic copper are welded to the end-caps. The resistors are coated with layers of blue color lacquer.

FEATURES

Power Rating	1/6W, 1/4W, 1/2W, 1W, 2W, 3W
Resistance Tolerance	$\pm 0.5\%$, $\pm 1\%$, $\pm 5\%$
T.C.R.	$\pm 15\text{ppm}/^{\circ}\text{C}$, $\pm 25\text{ppm}/^{\circ}\text{C}$, $\pm 50\text{ppm}/^{\circ}\text{C}$, $\pm 100\text{ppm}/^{\circ}\text{C}$


DERATING CURVE

For resistors operated in ambient temperatures above 70°C , power rating must be derated in accordance with the curve below.



DIMENSIONS

Unit: mm



STYLE		DIMENSION			
Normal	Miniature	L	øD	H	ød
MFR-12	MFR25S	3.4 ± 0.3	1.9 ± 0.2	28 ± 2.0	0.45 ± 0.05
MFR-25	MFR50S	6.3 ± 0.5	2.4 ± 0.2	28 ± 2.0	0.55 ± 0.05
MFR-50	MFR1WS	9.0 ± 0.5	3.3 ± 0.3	26 ± 2.0	0.55 ± 0.05
MFR100	MFR2WS	11.5 ± 1.0	4.5 ± 0.5	35 ± 2.0	0.8 ± 0.05
MFR200	MFR3WS	15.5 ± 1.0	5.0 ± 0.5	33 ± 2.0	0.8 ± 0.05

Note:

ELECTRICAL CHARACTERISTICS

STYLE	MFR-12	MFR25S	MFR-25	MFR50S	MFR-50	MFRIWS	MFRI00	MFR2WS	MFR200	MFR3WS
Power Rating at 70°C	1/6W	1/4W		1/2W		1W		2W		3W
Maximum Working Voltage	200V		250V	300V	350V	400V	500V			
Maximum Overload Voltage	400V		500V	600V	700V	800V	1,000V			
Voltage Proof on Insulation	300V	400V	500V			700V	1,000V			
Resistance Range	1Ω - 10MΩ & 0Ω for E24 & E96 series value									
Operating Temp. Range	-55°C to +155°C									
Temperature Coefficient	±15ppm/°C, ±25ppm/°C, ±50ppm/°C, ±100ppm/°C									

Note: Special value is available on request

ENVIRONMENTAL CHARACTERISTICS

PERFORMANCE TEST	TEST METHOD		APPRAISE
Short Time Overload	IEC 60115-1 4.13	2.5 times RCWV for 5 Sec.	±0.25%+0.05Ω
Voltage Proof on Insulation	IEC 60115-1 4.7	in V-block for 60 Sec., test voltage by type	By type
Temperature Coefficient	IEC 60115-1 4.8	-55°C to +155°C	By type
Insulation Resistance	IEC 60115-1 4.6	in V-block for 60 Sec.	>10,000MΩ
Solderability	IEC 60115-1 4.17	235±5°C for 3±0.5 Sec.	95% Min. coverage
Solvent Resistance of Marking	IEC 60115-1 4.30	IPA for 5±0.5 Min. with ultrasonic	No deterioration of coatings and markings
Robustness of Terminations	IEC 60115-1 4.16	Direct load for 10 Sec. in the direction of the terminal leads	≥2.5kg (24.5N)
Periodic-pulse Overload	IEC 60115-1 4.39	4 times RCWV 10,000 cycles (1 Sec. on, 25 Sec. off)	±1.0%+0.05Ω
Damp Heat Steady State	IEC 60115-1 4.24	40±2°C, 90-95% RH for 56 days, loaded with 0.1 times RCWV	±1.5%+0.05Ω
Endurance at 70°C	IEC 60115-1 4.25	70±2°C at RCWV for 1,000 Hr. (1.5 Hr. on, 0.5 Hr. off)	±1.5%+0.05Ω
Temperature Cycling	IEC 60115-1 4.19	-55°C ⇄ Room Temp. ⇄ +155°C ⇄ Room Temp. (5 cycles)	±0.75%+0.05Ω
Resistance to Soldering Heat	IEC 60115-1 4.18	260±3°C for 10±1 Sec., immersed to a point 3±0.5mm from the body	±0.25%+0.05Ω

Note: RCWV(Rated Continuous Working Voltage) = $\sqrt{\text{Power Rating} \times \text{Resistance Value}}$ or Max. working voltage listed above, whichever less.

Revision: 201304



EXPLANATIONS OF ORDERING CODE

MFR	-12	F	T	F	52-	100R
Code 1 - 3 Series Name See Index	Code 4 - 6 Power Rating -05 = $\varnothing$ d0.5mm -06 = $\varnothing$ d0.6mm -07 = $\varnothing$ d0.7mm -08 = $\varnothing$ d0.8mm -10 = $\varnothing$ d1.0mm -14 = $\varnothing$ d1.4mm -12 = 1/6W -25 = 1/4W 25S = 1/4WS -50 = 1/2W 50S = 1/2WS 100 = 1W 1WS = 1WS 200 = 2W 2WS = 2WS 204 = 0.4W 207 = 0.6W 300 = 3W 3WS = 3WS 3WM = 3WM 400 = 4W 500 = 5W 5WS = 5WS 5SS = 5WSS 700 = 7W 7WS = 7WS 10A = 10W 20A = 20W 30A = 30W 40A = 40W 50A = 50W 10S = 10WS 15A = 15W 25A = 25W 10B = 100W 25B = 250W	Code 7 Tolerance P = $\pm 0.02\%$ A = $\pm 0.05\%$ B = $\pm 0.1\%$ C = $\pm 0.25\%$ D = $\pm 0.5\%$ F = $\pm 1\%$ G = $\pm 2\%$ J = $\pm 5\%$ K = $\pm 10\%$ - = Base on Spec.	Code 8 Packing Style T = Tape/Box R = Tape/Reel B = Bulk	Code 9 Temperature Coefficient of Resistance - = Base on Spec. A = ± 5 ppm/ $^{\circ}$ C B = ± 10 ppm/ $^{\circ}$ C C = ± 15 ppm/ $^{\circ}$ C S = ± 20 ppm/ $^{\circ}$ C D = ± 25 ppm/ $^{\circ}$ C E = ± 50 ppm/ $^{\circ}$ C F = ± 100 ppm/ $^{\circ}$ C G = ± 200 ppm/ $^{\circ}$ C H = ± 250 ppm/ $^{\circ}$ C I = ± 300 ppm/ $^{\circ}$ C J = ± 350 ppm/ $^{\circ}$ C	Code 10 - 12 Forming Type 26- = 26mm 52- = 52.4mm 73- = 73mm 81- = 81mm 91- = 91mm F = F Type FK = FK Type FKK = FKK Type FFK = F-form Kink M = M-Type Forming MB = M-form W/flat MT = MT Type Forming MR = MR Type AV = AVIsert PN = PANAsert	Code 13 - 17 Resistance Value 0R1 = 0.1 100R = 100 10K = 10,000 10M = 10,000,000

EXCEPTION:

• Cement series:

<Code 8>: Special packing style code

B: Bulk with wirewound or metal oxide sub-assembly for resistance value

W: Bulk with ceramic based wirewound sub-assembly for resistance value

M: Bulk with metal oxide sub-assembly for resistance value

F: Bulk with Fiberglass based wirewound sub-assembly for resistance value

<Code 10-12>: Without forming code

Example: **SQP500JB-10R**

• JPW series:

<Code 13-17>: without resistance value code

Example: **JPW-06-T-52-**

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Yageo:

[MFR-25FBF52-23R](#) [MFR-25FBF52-23R5](#) [MFR-25FBF52-24R5](#) [MFR-25FBF52-25R](#) [MFR-25FBF52-26R](#) [MFR-25FBF52-26R5](#) [MFR-25FBF52-271R](#) [MFR-25FBF52-27K1](#) [MFR-25FBF52-27R5](#) [MFR-25FBF52-28R5](#) [MFR-25FBF52-29K1](#) [MFR-25FBF52-29R](#) [MFR-25FBF52-29R5](#) [MFR-25FBF52-2R5](#) [MFR-25FBF52-388R](#) [MFR-25FBF52-3K1](#) [MFR-25FBF52-3K15](#) [MFR-25FBF52-3K2](#) [MFR-25FBF52-3K25](#) [MFR-25FBF52-3K35](#) [MFR-25FBF52-3K45](#) [MFR-25FBF52-3K5](#) [MFR-25FBF52-3K55](#) [MFR-25FBF52-3K7](#) [MFR-25FBF52-3K75](#) [MFR-25FBF52-3K8](#) [MFR-25FBF52-3K85](#) [MFR-25FBF52-3K95](#) [MFR-25FBF52-3M57](#) [MFR-25FBF52-3R5](#) [MFR-25FBF52-407R](#) [MFR-25FBF52-481R](#) [MFR-25FBF52-48K5](#) [MFR-25FBF52-4K](#) [MFR-25FBF52-4K05](#) [MFR-25FBF52-4K1](#) [MFR-25FBF52-4K15](#) [MFR-25FBF52-4K2](#) [MFR-25FBF52-4K25](#) [MFR-25FBF52-4K35](#) [MFR-25FBF52-4K4](#) [MFR-25FBF52-4K45](#) [MFR-25FBF52-4K5](#) [MFR-25FBF52-4K55](#) [MFR-25FBF52-4K6](#) [MFR-25FBF52-4K65](#) [MFR-25FBF52-4K8](#) [MFR-25FBF52-4K85](#) [MFR-25FBF52-4K9](#) [MFR-25FBF52-4K95](#) [MFR-25FBF52-4R](#) [MFR-25FBF52-4R5](#) [MFR-25FBF52-505R](#) [MFR-25FBF52-50K](#) [MFR-25FBF52-530R](#) [MFR-25FBF52-556R](#) [MFR-25FBF52-569R](#) [MFR-25FBF52-597R](#) [MFR-25FBF52-5K](#) [MFR-25FBF52-5K2](#) [MFR-25FBF52-5K3](#) [MFR-25FBF52-5K4](#) [MFR-25FBF52-5K5](#) [MFR-25FBF52-5K7](#) [MFR-25FBF52-5K8](#) [MFR-25FBF52-5R](#) [MFR-25FBF52-5R5](#) [MFR-25FBF52-612R](#) [MFR-25FBF52-64K7](#) [MFR-25FBF52-6K](#) [MFR-25FBF52-6K45](#) [MFR-25FBF52-6K75](#) [MFR-25FBF52-6R](#) [MFR-25FBF52-6R5](#) [MFR-25FBF52-7R](#) [MFR-25FBF52-8R](#) [MFR-25FBF52-8R5](#) [MFR-25FBF52-9K](#) [MFR-25FBF52-9R](#) [MFR-25FBF52-9R5](#) [MFR-25FRF52-104K](#) [MFR-25FRF52-11R6](#) [MFR-25FRF52-194K](#) [MFR-25FRF52-19R](#) [MFR-25FRF52-1K67](#) [MFR-25FRF52-1M92](#) [MFR-25FRF52-214K](#) [MFR-25FRF52-3K29](#) [MFR-25FRF52-45K9](#) [MFR-25FRF52-4R](#) [MFR-25FRF52-52R4](#) [MFR-25FRF52-59R9](#) [MFR-25FRF52-60K](#) [MFR-25FRF52-60K2](#) [MFR-25FRF52-75K9](#) [MFR-25FRF52-7K8](#) [MFR-25FTE52-0R33](#) [MFR-25FTE52-0R45](#) [MFR-25FTE52-0R5](#) [MFR-25FTE52-104K](#)