

Part Number: **0527450496**
Status: **Contact Molex**
Description: 0.50mm (.020") Pitch FFC/FPC Connector, Right Angle, SMT, ZIF, Top Contact Style, 4 Circuits, Lead-free, High Barrier Packaging

Documents:

3D Model	Application Specification AS-52745-001 (PDF)
Drawing (PDF)	Packaging Specification SPK-52745-002 (PDF)
Product Specification PS-52745-050 (PDF)	RoHS Certificate of Compliance (PDF)

Agency Certification

UL	E29179
----	--------

General

Product Family	FFC/FPC Connectors
Series	<u>52745</u>
Product Name	N/A

Physical

Circuits (Loaded)	4
Color - Resin	Black, White
Contact Position	Top
Durability (mating cycles max)	20
Entry Angle	90° Angle
Flammability	94V-0
Mated Height	2.00mm (.079")
Material - Metal	Phosphor Bronze
Material - Plating Mating	Tin-Bismuth
Material - Plating Termination	Tin-Bismuth
Number of Rows	1
Orientation	Right Angle
PCB Locator	No
PCB Retention	Yes
Packaging Type	Embossed Tape on Reel
Pitch - Mating Interface	0.50mm (.020")
Polarized to PCB	Yes
Stackable	No
Temperature Range - Operating	-20°C to +85°C
Termination Interface: Style	Surface Mount
Wire/Cable Type	FFC/FPC

Electrical

Current - Maximum per Contact	0.5A
Voltage - Maximum	50V

Material Info

Reference - Drawing Numbers

Application Specification	AS-52745-001
Packaging Specification	SPK-52745-002
Product Specification	PS-52745-050, RPS-52745-048, RPS-52745-049, RPS-52745-051, RPS-52745-059, RPS-52745-067, RPS-52745-069, RPS-52745-070, RPS-52745-073
Sales Drawing	SD-52745-048, SD-52745-049



EU RoHS
ELV and
Compliance
REACH
Contains
Low-Hal
Not Low

Need more
environm

Email pro
For a mu
Compliance

Please v
non-prod

Search
52745

This document was generated on 05/05/2011

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION