

Low Pass Filter

Features

- excellent power handling
- small size
- 7 sections
- temperature stable
- LTCC construction , and has good moisture resistance, corrosion resistance, high reliability.

Applications



- harmonic rejection
- VHF/UHF transmitters/receivers
- Base Station of Mobile Communication, lab use.

Electrical Specifications at 25°C


Parameter		Frequency(MHz)	Min.	Typ.	Max.	Unit
Pass Band	Insertion Loss Freq.Cut-Off VSWR	DC-2600	-	1.1	1.3	dB
		2800	-	3.0	-	dB
		DC-2600	-	1.2	1.5	:1
Stop Band	Rejection Loss VSWR	3560	25	30	-	dB
		3900-8000	25	35	-	dB
		8400	20	30	-	dB
		3560-8400	-	20	-	:1

Typical Performance Data at 25°C

Frequency (MHz)	Insertion Loss (dB)	VSWR (:1)
50	0.04	1.01
500	0.13	1.10
1000	0.22	1.16
2000	0.49	1.22
2500	1.19	1.33
2820	3.02	1.99
3000	12.00	8.89
3500	28.37	29.96
4000	48.66	39.70
5000	41.05	50.04
6000	34.38	62.86
7000	35.24	42.39
8000	40.11	27.99
9000	25.35	27.32
10000	17.31	15.31



Suggested PCB Layout




NOTES: 1. COPLANAR WAVEGUIDE PARAMETERS ARE SHOWN FOR ROGERS RO4350 WITH THICKNESS .508" $\pm$.0015".
COPPER: 1/2 OZ. EACH SIDE.
FOR OTHER MATERIALS TRACE WIDTH & GAP MAY NEED TO BE MODIFIED.

2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.

 DENOTES PCB COPPER LAYOUT WITH SMOBC
(SOLDER MASK OVER BARE COPPER)

 DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK

JY-LFCN-2600+




50Ω DC to 2600 MHz

Maximum Ratings

Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C
RF Power Input*	10W max. at 25°C

* Passband rating, derate linearly to 3.5W at 100°C ambient.
Permanent damage may occur if any of these limits are exceeded.




Electrical Schematic



Pin Connections

RF IN	1
RF OUT	3
GROUND	2,4

Outline Drawing



Outline Dimensions: Unit ([mm](#))

A	3.20	B	1.60	C	0.95
D	0.51	E	0.81	F	0.23
G	4.29	H	2.21	J	0.61
K	3.10	L	0.61	M	2.21
N	0.30	P	1.80	net	0.02g