





# Chip Inductors – 0603LS (1608)

- Higher inductance values than other 0603 inductors
- Ferrite construction for high current handling
- Inductance values: 47 nH – 22  $\mu$ H; 5% and 2% tolerance

## Typical L vs Frequency



## Typical Q vs Frequency



**Designer's Kit C347** contains 10 each of all 5% values

**Core material** Ceramic/Ferrite

**Terminations** RoHS compliant silver-palladium-platinum-glass frit. Other terminations available at additional cost.

**Weight** 4.8 – 6.2 mg

**Ambient temperature** –40°C to +85°C with Irms current, +85°C to +100°C with derated current

**Storage temperature** Component: –40°C to +100°C. Tape and reel packaging: –40°C to +80°C

**Resistance to soldering heat** Max three 40 second reflows at +260°C, parts cooled to room temperature between cycles

**Temperature Coefficient of Inductance (TCL)** +50 to +150 ppm/°C

**Moisture Sensitivity Level (MSL)** 1 (unlimited floor life at <30°C / 85% relative humidity)


**Failures in Time (FIT) / Mean Time Between Failures (MTBF)**

One per billion hours / one billion hours, calculated per Telcordia SR-332

**Packaging** 2000 per 7" reel. Plastic tape: 8 mm wide, 0.23 mm thick, 4 mm pocket spacing, 1.17 mm pocket depth

**PCB washing** Only pure water or alcohol recommended

## Irms Derating



www.coilcraft.com

**US** +1-847-639-6400 sales@coilcraft.com  
**UK** +44-1236-730595 sales@coilcraft-europe.com  
**Taiwan** +886-2-2264 3646 sales@coilcraft.com.tw  
**China** +86-21-6218 8074 sales@coilcraft.com.cn  
**Singapore** + 65-6484 8412 sales@coilcraft.com.sg

Document 264-1 Revised 01/18/12

© Coilcraft Inc. 2012

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check out web site for latest information.



# Chip Inductors – 0603LS Series

**S-Parameter files**

ON OUR WEB SITE

**SPICE models**

ON OUR WEB SITE

| Part number <sup>1</sup> | Inductance <sup>2</sup><br>(nH) | Percent<br>tolerance | Q min <sup>3</sup> | SRF min <sup>4</sup><br>(MHz) | DCR max <sup>5</sup><br>(Ohms) | I <sub>rms</sub> <sup>6</sup><br>(A) | Color<br>code | Overall<br>width |
|--------------------------|---------------------------------|----------------------|--------------------|-------------------------------|--------------------------------|--------------------------------------|---------------|------------------|
| 0603LS-47NX_L_           | 47 @ 7.9 MHz                    | <b>5,2</b>           | 12 @ 7.9 MHz       | 1500                          | 0.075                          | 1.40                                 | Black         | B1               |
| 0603LS-51NX_L_           | 51 @ 7.9 MHz                    | <b>5,2</b>           | 12 @ 7.9 MHz       | 1400                          | 0.075                          | 1.00                                 | Violet        | B1               |
| 0603LS-72NX_L_           | 72 @ 7.9 MHz                    | <b>5,2</b>           | 12 @ 7.9 MHz       | 1400                          | 0.12                           | 1.40                                 | Brown         | B1               |
| 0603LS-101X_L_           | 100 @ 7.9 MHz                   | <b>5,2</b>           | 12 @ 7.9 MHz       | 1150                          | 0.13                           | 1.40                                 | Red           | B1               |
| 0603LS-121X_L_           | 120 @ 7.9 MHz                   | <b>5,2</b>           | 12 @ 7.9 MHz       | 1100                          | 0.15                           | 1.40                                 | Orange        | B1               |
| 0603LS-151X_L_           | 150 @ 7.9 MHz                   | <b>5,2</b>           | 15 @ 7.9 MHz       | 1050                          | 0.15                           | 1.30                                 | Yellow        | B1               |
| 0603LS-181X_L_           | 180 @ 7.9 MHz                   | <b>5,2</b>           | 15 @ 7.9 MHz       | 950                           | 0.15                           | 1.30                                 | Green         | B1               |
| 0603LS-241X_L_           | 240 @ 7.9 MHz                   | <b>5,2</b>           | 15 @ 7.9 MHz       | 800                           | 0.16                           | 0.95                                 | Violet        | B1               |
| 0603LS-271X_L_           | 270 @ 7.9 MHz                   | <b>5,2</b>           | 15 @ 7.9 MHz       | 775                           | 0.30                           | 0.71                                 | Gray          | B1               |
| 0603LS-331X_L_           | 330 @ 7.9 MHz                   | <b>5,2</b>           | 15 @ 7.9 MHz       | 725                           | 0.46                           | 0.56                                 | White         | B1               |
| 0603LS-391X_L_           | 390 @ 7.9 MHz                   | <b>5,2</b>           | 15 @ 7.9 MHz       | 620                           | 0.51                           | 0.50                                 | Black         | B1               |
| 0603LS-471X_L_           | 470 @ 7.9 MHz                   | <b>5,2</b>           | 15 @ 7.9 MHz       | 540                           | 0.62                           | 0.42                                 | Brown         | B1               |
| 0603LS-561X_L_           | 560 @ 7.9 MHz                   | <b>5,2</b>           | 15 @ 7.9 MHz       | 525                           | 0.44                           | 0.55                                 | Red           | B1               |
| 0603LS-681X_L_           | 680 @ 7.9 MHz                   | <b>5,2</b>           | 15 @ 7.9 MHz       | 260                           | 0.52                           | 0.47                                 | Orange        | B2               |
| 0603LS-781X_L_           | 780 @ 7.9 MHz                   | <b>5,2</b>           | 15 @ 7.9 MHz       | 460                           | 0.83                           | 0.39                                 | Yellow        | B1               |
| 0603LS-821X_L_           | 820 @ 7.9 MHz                   | <b>5,2</b>           | 15 @ 7.9 MHz       | 410                           | 0.69                           | 0.40                                 | Green         | B2               |
| 0603LS-102X_L_           | 1000 @ 7.9 MHz                  | <b>5,2</b>           | 15 @ 7.9 MHz       | 190                           | 0.81                           | 0.40                                 | Blue          | B2               |
| 0603LS-122X_L_           | 1200 @ 7.9 MHz                  | <b>5,2</b>           | 15 @ 7.9 MHz       | 160                           | 0.87                           | 0.37                                 | Violet        | B2               |
| 0603LS-152X_L_           | 1500 @ 7.9 MHz                  | <b>5,2</b>           | 15 @ 7.9 MHz       | 100                           | 0.96                           | 0.35                                 | Gray          | B2               |
| 0603LS-182X_L_           | 1800 @ 7.9 MHz                  | <b>5,2</b>           | 15 @ 7.9 MHz       | 80                            | 1.1                            | 0.35                                 | White         | B2               |
| 0603LS-222X_L_           | 2200 @ 7.9 MHz                  | <b>5,2</b>           | 15 @ 7.9 MHz       | 68                            | 1.2                            | 0.32                                 | Black         | B2               |
| 0603LS-272X_L_           | 2700 @ 7.9 MHz                  | <b>5,2</b>           | 15 @ 7.9 MHz       | 60                            | 1.5                            | 0.28                                 | Brown         | B2               |
| 0603LS-332X_L_           | 3300 @ 7.9 MHz                  | <b>5,2</b>           | 15 @ 7.9 MHz       | 42                            | 1.5                            | 0.28                                 | Red           | B2               |
| 0603LS-392X_L_           | 3900 @ 7.9 MHz                  | <b>5,2</b>           | 15 @ 7.9 MHz       | 40                            | 1.6                            | 0.28                                 | Orange        | B2               |
| 0603LS-472X_L_           | 4700 @ 7.9 MHz                  | <b>5,2</b>           | 15 @ 7.9 MHz       | 34                            | 2.1                            | 0.26                                 | Yellow        | B2               |
| 0603LS-562X_L_           | 5600 @ 7.9 MHz                  | <b>5,2</b>           | 15 @ 7.9 MHz       | 32                            | 2.6                            | 0.24                                 | Green         | B2               |
| 0603LS-682X_L_           | 6800 @ 7.9 MHz                  | <b>5,2</b>           | 15 @ 7.9 MHz       | 31                            | 3.1                            | 0.20                                 | Black         | B2               |
| 0603LS-782X_L_           | 7800 @ 7.9 MHz                  | <b>5,2</b>           | 15 @ 7.9 MHz       | 28                            | 3.5                            | 0.20                                 | Blue          | B2               |
| 0603LS-822X_L_           | 8200 @ 7.9 MHz                  | <b>5,2</b>           | 15 @ 7.9 MHz       | 26                            | 3.6                            | 0.19                                 | Violet        | B2               |
| 0603LS-103X_L_           | 10,000 @ 2.5 MHz                | <b>5,2</b>           | 12 @ 2.5 MHz       | 25                            | 4.8                            | 0.18                                 | Gray          | B2               |
| 0603LS-153X_L_           | 15,000 @ 2.5 MHz                | <b>5,2</b>           | 20 @ 2.5 MHz       | 23                            | 7.1                            | 0.17                                 | White         | B2               |
| 0603LS-183X_L_           | 18,000 @ 2.5 MHz                | <b>5,2</b>           | 20 @ 2.5 MHz       | 22                            | 7.6                            | 0.16                                 | Brown         | B2               |
| 0603LS-223X_L_           | 22,000 @ 2.5 MHz                | <b>5,2</b>           | 22 @ 2.5 MHz       | 19                            | 8.81                           | 0.13                                 | Black         | B2               |

1. When ordering, specify **tolerance, termination and packaging** codes:

**0603LS-822XJLC**

**Tolerance:** G = 2% J = 5% (Table shows stock tolerances in bold.)

**Termination:** L = RoHS compliant silver-palladium-platinum-glass frit. Special order: T = RoHS tin-silver-copper (95.5/4/0.5) or S = non-RoHS tin-lead (63/37).

**Packaging:** C = 7" machine-ready reel. EIA-481 embossed plastic tape (2000 parts per full reel).

B = Less than full reel. In tape, but not machine ready. To have a leader and trailer added (\$25 charge), use code letter C instead.

2. Inductance measured at 0.1 Vrms, using Coilcraft SMD-A fixture in Agilent/HP 4286A impedance analyzer with Coilcraft-provided correlation pieces.

3. Q measured on Agilent/HP 4395A with Agilent/HP 16193 test fixture.


4. SRF measured using Agilent/HP 8753D network analyzer with Coilcraft SMD-D test fixture.

5. DCR measured on Cambridge Technology Micro-ohmmeter.

6. Current that causes a 15°C temperature rise from 25°C ambient. Because of their open construction, these parts will not saturate.

7. Electrical specifications at 25°C.

Refer to Doc 362 "Soldering Surface Mount Components" before soldering.



| A max | B        | C max | D ref | E     | F     | G     | H     | I     | J            |
|-------|----------|-------|-------|-------|-------|-------|-------|-------|--------------|
| 0.071 | See note | 0.044 | 0.015 | 0.030 | 0.013 | 0.034 | 0.040 | 0.025 | 0.025 inches |
| 1,80  |          | 1,12  | 0,38  | 0,76  | 0,33  | 0,86  | 1,02  | 0,64  | 0,64 mm      |

**Note:** B1 = 0.040 ±0.004 in / 1,016 ±0,102 mm  
B2 = 0.046 ±0.004 in / 1,169 ±0,102 mm

Height dimension (C) is before optional solder application. For maximum height dimension including solder, add 0.006 in / 0,152 mm.