



In case	TO

2	PHOSPHOR BRONZE	4	5	PS	PLASTIC REEL (BLACK)
1	LCP	UL94V-0, BLACK	4	POLYESTER	CLEAR (COVER TAPE)
NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS
CODE NO. (OLD)		DRAWN	DESIGNED	CHECKED	APPROVED
		F. MATSUKI	A. TAKAHASHI	T. SAKATA	T. SAKATA
		'05. 01. 27	'05. 01. 28	'05. 01. 31	'05. 01. 31
		DRAWING NO.	PART NO.		
SCALE		EDC3-303169-05	DF30FC-60DS-0.4V(81)		
FREE					
UNITS		 HIROSE ELECTRIC CO., LTD	CODE NO.		1/2
mm			CL684-1082-3-81		



NOTE 1. ALL LEADS CO-PLANARITY SHALL BE 0.1 MAX.

2. PER REEL : 5000 CONNECTORS.

3. AT THE BEGINNING OF THE REEL, 100 MM AT MIN SHALL BE EMPTY POCKETS.
AT THE END OF THE REEL, 160 MM AT MIN SHALL BE EMPTY POCKETS.

4. CONTACT PLATING SPECIFICATIONS.

CONTACT AREA : GOLD 0.05 μ m MIN.

SMT LEAD : GOLD 0.02 μ m MIN.

UNDERPLATING : NICKEL 1 μ m MIN.

(SURFACE : SEALING)

Jun.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

TO

