



**7030**

## COMPACT FLOW REGULATORS, EXHAUST for metric tubing

[Zoom](#)

[Description](#)  
[Dimensions](#)  
[Specifications](#)  
[CAD drawings](#)  
[Related products](#)

[Display Part No for imperial tubing](#)  
 convert weight standard : kg | [oz](#)

		ØD (mm)	F (mm)	H (mm)	Hmaxi (mm)	H1 (mm)	H2 (mm)	J (mm)	L (mm)	 (kg)
7030 06 00		6	10,0	35,0	41,0	14,0	17,0	16,0	22,0	0,013
7030 08 00		8	14,0	39,5	46,5	16,0	21,5	19,0	28,0	0,022
7030 10 00		10	17,0	43,5	51,5	17,5	24,5	23,0	31,5	0,039
7030 12 00		12	17,0	43,0	51,0	17,0	27,0	23,0	31,5	0,044



# 7030

## COMPACT FLOW REGULATORS, EXHAUST

[Description](#)  
[Dimensions](#)  
[Specifications](#)  
[CAD drawings](#)  
[Related products](#)

maximum working pressure	bar 10	MPa 1	psi 145
working temperature	°C (Celsius) From 0 to 70	F (Fahrenheit) From 32 to 158	K (Kelvin) From 273 to 343
body	engineering grade polymer		
'O'-rings	nitrile		
screw	nickel-plated brass		