



**Product:** [5000UE](#)

Security & Sound, 2 Conductor 12 AWG, BC, Unshielded, CL3R-FPLR

**Product Description**  
Security & Commercial Audio Cable, Riser-CL3R-FPLR 2-12 AWG stranded bare copper conductors with polypropylene insulation, PVC jacket with ripcord

**Technical Specifications**

**Product Overview**

|                        |                                                                            |
|------------------------|----------------------------------------------------------------------------|
| Suitable Applications: | Security System, Intercom/PA, Audio/Speaker, Fire Alarm Systems (Red only) |
|------------------------|----------------------------------------------------------------------------|

**Construction Details**

| Element      | No. of Elements | Size   | Stranding | Material         |
|--------------|-----------------|--------|-----------|------------------|
| Conductor(s) | 2               | 12 AWG | 19x25     | BC - Bare Copper |

| Element      | Material           | Nom. Thickness     | Nom. Insulation Diameter | Color Code   |
|--------------|--------------------|--------------------|--------------------------|--------------|
| Conductor(s) | PP - Polypropylene | 0.011 in (0.28 mm) | 0.113 in (2.87 mm)       | Black, White |

**Outer Shield**

| Material  |
|-----------|
| No Shield |

| Material                 | Nom. Thickness     | Nom. Diameter    | Ripcord |
|--------------------------|--------------------|------------------|---------|
| PVC - Polyvinyl Chloride | 0.017 in (0.43 mm) | 0.26 in (6.6 mm) | Yes     |

|                                   |                  |
|-----------------------------------|------------------|
| Overall Cable Diameter (Nominal): | 0.26 in (6.6 mm) |
|-----------------------------------|------------------|

**Electrical Characteristics**

| Element      | Nom. Conductor DCR | Nom. Capacitance Cond-to-Cond | Max. Current                 |
|--------------|--------------------|-------------------------------|------------------------------|
| Conductor(s) | 1.6 Ohm/1000ft     | 24 pF/ft (79 pF/m)            | 30 Amps per conductor @ 30°C |

| UL Voltage Rating |
|-------------------|
| 300 V             |

**Mechanical Characteristics**

| UL Temperature | Operating      |
|----------------|----------------|
| 75°C           | -20°C to +75°C |

| Stationary Min. | Installation Min. |
|-----------------|-------------------|
| 2.6 in (66 mm)  | 2.6 in (66 mm)    |

|                    |                   |
|--------------------|-------------------|
| Max. Pull Tension: | 152 lbs (68.9 kg) |
|--------------------|-------------------|

|                    |               |
|--------------------|---------------|
| Bulk Cable Weight: | 51 lbs/1000ft |
|--------------------|---------------|

### Standards and Compliance

|                                  |                                                                              |
|----------------------------------|------------------------------------------------------------------------------|
| Environmental Suitability:       | Indoor - Riser, Indoor                                                       |
| Flammability / Reaction to Fire: | UL 1666 Riser, IEEE 1202 FT4, IEC 60332-1-2                                  |
| CPR Compliance:                  | CPR Euroclass: Eca                                                           |
| NEC / UL Compliance:             | Article 725, Article 760, CL3R, FPLR                                         |
| European Directive Compliance:   | EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE) |
| UK Regulation Compliance:        | UKCA Mark                                                                    |
| APAC Compliance:                 | China RoHS II (GB/T 26572-2011)                                              |
| Plenum Number:                   | 6000UE                                                                       |

### History

|                      |                                                  |
|----------------------|--------------------------------------------------|
| Update and Revision: | Revision Number: 0.518 Revision Date: 02-15-2024 |
|----------------------|--------------------------------------------------|

### Part Numbers

#### Variants

| Item #          | Color | Putup Type   | Length   | UPC          | Footnote |
|-----------------|-------|--------------|----------|--------------|----------|
| 5000UE 010Z500  | Black | ReelTuff Box | 500 ft   | 612825434085 |          |
| 5000UE 010I000  | Black | Reel         | 1,000 ft | 612825154600 | C        |
| 5000UE 010Z1000 | Black | ReelTuff Box | 1,000 ft | 612825432883 |          |
| 5000UE 010Z1000 | Black | ReelTuff Box | 1,000 ft | 612825432883 |          |
| 5000UE 010S000  | Black | Reel         | 5,000 ft | 612825437864 |          |
| 5000UE 008500   | Gray  | Reel         | 500 ft   | 612825154594 | C        |
| 5000UE 008Z500  | Gray  | ReelTuff Box | 500 ft   | 612825434061 |          |
| 5000UE 008I000  | Gray  | Reel         | 1,000 ft | 612825336310 | C        |
| 5000UE 008Z1000 | Gray  | ReelTuff Box | 1,000 ft | 612825432869 |          |
| 5000UE 008Z1000 | Gray  | ReelTuff Box | 1,000 ft | 612825432869 |          |
| 5000UE 002I000  | Red   | Reel         | 1,000 ft | 612825154587 | C        |
| 5000UE 002Z1000 | Red   | ReelTuff Box | 1,000 ft | 612825432852 |          |
| 5000UE 002Z1000 | Red   | ReelTuff Box | 1,000 ft | 612825432852 |          |

© 2024 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.