


REVISIONS					
REV.	ECN NO.	LOCATION	DESCRIPTION	DATE	DESIGN
A0	N/A		INITIAL RELEASE	/	/
A1	N/A		图面升级整理图面	2024.9.10	阿树

- SPECIFICATIONS
- Voltage rating:250V AC/DC
 - Current rating:2A AC/DC
 - Withstanding Voltage:800V AC/minute
 - Temperature range:-40°C~+125°C
 - Insulation resistance:≥1000MΩ
 - Contact resistance:≤20mΩ

PART NO.:

X2016 I F-P SN
① ② ③ ④ ⑤

- ①Series No
②Category:T-Terminal
③F-Female
④Material:P-Phosphor bronze
⑤Plating style:SN-Bright tin plating



X2016TF-PSN	Phosphor bronze	AWG#24-30	Tin plating	X2016HM
PARY NO	Matrial	Wire range	Finish	Suitable XKB Housing

AuGLAR	±5°
X.	±0.40
X.x	±0.30
X.xx	±0.20
X.xxx	±0.15
UNSPECIFIED TOLERAuces	



DESIGN	阿树
CHECKED	
APPROVED	

VIEW:	
UNIT:	mm/in
SIZE:	A4

MODEL TYPE:	2.00mm Crimp Style Connectors
PART NO.:	X2016TF-PSN
DWG NO.:	

SCALE	PAGE	REVISION
N/A	1/1	A1