

product type designation



Power Supply SCALANCE PS924 PoE

SCALANCE PS9230 PoE power supply for Power-over-Ethernet, Input: 120/230 V AC, Output: 54 V DC/1.6 A NEC Class 2

type of current supply	Input: AC 120 / 230 V, Output: DC 54 V / 1.6 A, NEC CLASS 2
suitability for use	Power supply for PoE
electrical data / input	
voltage curve / at input	AC single phase
supply voltage / rated value	230 V
supply voltage / rated value	85 ... 264 V
type of voltage / of the supply voltage	AC
consumed current / at rated supply voltage / maximum	1 A
design of input / wide range input	Yes
overvoltage category	Category II
buffering time / for rated value of the output current / in the event of power failure / minimum	50 ms
line frequency	• 50 Hz • 60 Hz • 1 / rated value • 2 / rated value
line frequency	47 ... 63 Hz
input current / at rated input voltage 230 V / rated value	1 A
current limitation / of inrush current / at 25 °C / maximum	35 A
fuse protection type / at input	Fuse T 3.15A soldered
electrical data / output	
voltage curve / at output	Controlled, isolated DC voltage, adjustable from 48 V to 54 V
output voltage / at DC / rated value	54 V
display version / for normal operation	LED green for DC ok
behavior of the output voltage / when switching on	Overshoot of $U_a < 2 \%$
startup delay time / maximum	1.5 s
voltage increase time / of the output voltage / maximum	15 ms
output current	• rated value • rated range
supplied active power / typical	86 W
product feature / parallel switching of channels	No
number of parallel-switched equipment resources / for increasing the power	0
efficiency in percent	89 %
power loss [W]	11 W

electrical data / closed-loop control	
relative overall tolerance / of the voltage	1 %
residual ripple / maximum	0.05 V
voltage peak / maximum	0.2 V
relative control precision / of the output voltage	
• on slow fluctuation of input voltage	0.2 %
• on slow fluctuation of ohm loading	0.5 %
• load step of resistive load 50/100/50 % / typical	0.5 %
• with rapid fluctuation of the input voltage by +/- 15% / typical	0.3 %
setting time	
• load step 50 to 100% / typical	0.5 ms
• load step 100 to 50% / typical	0.5 ms
electrical data / protection and monitoring	
design of the overvoltage protection / at output	< 60 V
response value current limitation / typical	1.7 A
property of the output / short-circuit proof	Yes
design of short-circuit protection	Electronic shutdown, automatic restart
electrical data / safety	
galvanic isolation / between input and output	Yes
galvanic isolation	Safety extra-low output voltage U _{out} acc. to EN 60950-1
operating resource protection class	Class I
leakage current	
• maximum	3.5 mA
• typical	2 mA
interfaces	
number of electrical connections	
• for power supply	3
• for signaling contact	2
type of electrical connection	
• for signaling contact	Screw terminal 0.5 - 2.5 mm ²
• at input	PE / L / N screw-type terminal 0.5 - 2.5 mm ²
• at output	2x + / 2x - , screw-type terminal 0.5 - 2.5 mm ²
signal inputs/outputs	
product component / signaling contact	Yes
relay design	Normal open contact (N/O)
operating voltage / of the signaling contacts	
• at DC / rated value	24 V
• at DC / maximum	60 V
operational current / of the signaling contacts	
• at DC / maximum	0.3 A
• at DC / at 30 V / maximum	0.3 A
design, dimensions and weights	
width	42 mm
height	125 mm
depth	125 mm
net weight	0.5 kg
product feature / of the enclosure / housing can be lined up	Yes
fastening method	
• 19-inch installation	No
• wall mounting	No
• 35 mm top hat DIN rail mounting	Yes
• S7-300 rail mounting	No
ambient conditions	
ambient temperature	
• during operation	-40 ... +70 °C
• during storage	-40 ... +85 °C

• during transport • note	-40 ... +85 °C
relative humidity / at 25 °C / without condensation / during operation / maximum	Convection
environmental category / acc. to IEC 60721	95 %
protection class IP	Climate class 3K3, without condensation
standards, specifications, approvals	
standard	IP20
• for safety / from CSA and UL • for emitted interference • for interference immunity	cULus listed (UL508, CSA C22.2 No. 107.1) EN 61000-6-4: 2007 EN 61000-6-2
certificate of suitability	EN 61000-6-4: 2007
• CE marking • C-Tick	Yes Yes
further information / internet-Links	
Internet-Link	
• to web page: selection aid TIA Selection Tool • to website: Industrial communication • to website: Industry Mall • to website: Information and Download Center • to website: Image database • to website: CAX-Download-Manager • to website: Industry Online Support	http://www.siemens.com/snst http://www.siemens.com/simatic-net https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter http://automation.siemens.com/bilddb http://www.siemens.com/cax https://support.industry.siemens.com
last modified:	12/18/2020 