

AUTOMOTIVE SEALS & CAVITY PLUGS









✓ Active

TE CONNECTIVITY (TE) **RUBBER PLUG**

282081-2

TE Internal Number: 282081-2

Not Yet Reviewed for EU RoHS Not Yet Reviewed for EU ELV

Seal Type Cavity Blanking Plug

Cavity Diameter 5.5 mm [.217 in]

Material Silicone

Resistance to Hydrocarbons POOR

Shore A Hardness 50



PRODUCT DRAWING

English



★ 3D PDF

DOCUMENTATION

Product Drawings

CAVITY PLUG FOR AMP SUPERSEAL 1,5 SRS. CONNECTORS

PDF

English

CAD Files

3D PDF

PDF

3D

Customer View Model

2D_DXF.ZIP

English

| Customer View Model 3D_STP.ZIP English | |
|---|---|
| FEATURES | + |
| Please review product documents or contact us for the latest agency approval information. | |
| Please Note: Use the Product Drawing for all design activity. | |
| Product Type Features | |
| Seal Type Cavity Blanking Plug | |
| Body Features | |
| Material Silicone Color Yellow | |
| Dimensions | |
| Cavity Diameter 5.5 mm [.217 in] | |
| Usage Conditions | |
| Operating Temperature Range -40 – 130 °C [-40 – 266 °F] | |
| Industry Standards | |
| UL Flammability Rating None | |
| Other | |
| Resistance to Hydrocarbons POOR Shore A Hardness 50 Lubricant Content No | |
| Statement of Compliance | |
| Statement of Compliance PDF | |
| | |

Customer View Model

3D_IGS.ZIP

English