





	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
	△				. .		△				. .
	△				. .		△				. .
	△				. .		△				. .

RECOMMEND PC BOARD HOLE PATTERN (MOUNTING SIDE)



PART No.	CODE No.		A	B	C	D
FX2B-20P-1, 27DS(71)	CL572-0701-0-71	20	30.33	11.43	18.05	10
FX2B-32P-1, 27DS(71)	CL572-0702-2-71	32	37.95	19.05	25.67	16
FX2B-40P-1, 27DS(71)	CL572-0703-5-71	40	43.03	24.13	30.75	20
FX2B-52P-1, 27DS(71)	CL572-0704-8-71	52	50.65	31.75	38.37	26
FX2B-60P-1, 27DS(71)	CL572-0705-0-71	60	55.73	36.83	43.45	30
FX2B-68P-1, 27DS(71)	CL572-0706-3-71	68	60.81	41.91	48.53	34
FX2B-80P-1, 27DS(71)	CL572-0707-6-71	80	68.43	49.53	56.15	40
FX2B-100P-1, 27DS(71)	CL572-0708-9-71	100	81.13	62.23	68.85	50

NOTES

1  STANDOFF DIFFERS ACCORDING TO PRODUCTS.

2. THE DIMENSIONS IN PARENTHESES ARE FOR REFERENCE.

3  NUMBER OF PIN.

1, 2	POLYAMIDE	BLACK	UL94V-0	3~6	PHOSPHOR BRONZE	CONTACT AREA:GOLD 0.2μ m min DIP AREA:TIN-PLATING 2μ m min UNDER PLATING:NICKEL 2μ m min				
NO.	MATERIAL	FINISH,	REMARKS	NO.	MATERIAL	FINISH,		REMARKS		
CODE NO. (OLD) CL						DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
						I. OKAYAMA	K. NAKAMURA	H. OKAWA	H. OKAWA	
						04.06.02	04.06.02	04.06.14	04.06.14	

	DRAWING NO.		PART NO.	
SCALE	EDC3-082283-21		FX2B-※※P-1.27DS(71)	
FREE	 HIROSE ELECTRIC CO.,LTD.		CODE NO.	
UNITS			CL572	
mm			1	1