

General Description:

The LWN2005AS uses trench technology and design to provide excellent $R_{DS(ON)}$ with low gate charge. It can be used in a wide variety of applications. The package form is SOP-8, which accords with the ROHS standard and Halogen Free standard.

Features:

- Fast Switching
- Low Gate Charge and $R_{DS(ON)}$
- Low Reverse transfer capacitances

Applications:

- DC-DC converter
- Portable Equipment
- Power Management

100% DVDS Tested

100% Avalanche Tested



Package Marking and Ordering Information:

Marking	Part Number	Package	Packing	Qty.
N2005/LW AS/D.C.	LWN2005AS	SOP-8	Reel	4000 Pcs

Absolute Maximum Ratings:


Symbol	Parameter		Value	Units
V_{DSS}	Drain-to-Source Voltage		20	V
I_D	Continuous Drain Current	$T_C=25^{\circ}C$	20	A
	Continuous Drain Current	$T_C=100^{\circ}C$	12.6	A
I_{DM}^{a1}	Pulsed Drain Current		80	A
E_{AS}^{a2}	Single pulse avalanche energy		55	mJ
V_{GS}	Gate-to-Source Voltage		± 10	V
P_D	Power Dissipation		2.5	W
T_J, T_{STG}	Operating Junction and Storage Temperature Rang		150, -55 to 150	$^{\circ}C$
T_L	Maximum Temperature for Soldering		260	$^{\circ}C$

Thermal Characteristics:


Symbol	Parameter	Value	Units
$R_{\theta JA}^{a3}$	Thermal Resistance, Junction-to-Ambient	50	$^{\circ}C/W$

V_{DSS}	20	V
I_D	20	A
P_D	2.5	W
$R_{DS(ON)}$ TYPE	3.4	m Ω

Marking and Pin Assignment



Inner Equivalent Principium Chart



Electrical Characteristic ($T_A = 25\text{ }^{\circ}\text{C}$, unless otherwise specified):

Static Characteristics						
Symbol	Parameter	Test Conditions	Value			Units
			Min.	Typ.	Max.	
V_{DSS}	Drain to Source Breakdown Voltage	$V_{GS}=0V, I_D=250\mu A$	20	--	--	V
I_{DSS}	Drain to Source Leakage Current	$V_{DS}=20V, V_{GS}=0V$	--	--	1.0	μA
$I_{GSS(F)}$	Gate to Source Forward Leakage	$V_{GS}=+10V, V_{DS}=0V$	--	--	100	nA
$I_{GSS(R)}$	Gate to Source Reverse Leakage	$V_{GS}=-10V, V_{DS}=0V$	--	--	-100	nA
$V_{GS(TH)}$	Gate Threshold Voltage	$V_{DS}=V_{GS}, I_D=250\mu A$	0.45	0.68	1.0	V
$R_{DS(ON)1}$	Drain-to-Source On-Resistance	$V_{GS}=4.5V, I_D=20A$	--	3.4	4.5	$m\Omega$
$R_{DS(ON)2}$	Drain-to-Source On-Resistance	$V_{GS}=2.5V, I_D=15A$	--	4.3	6.0	$m\Omega$

Dynamic Characteristics						
Symbol	Parameter	Test Conditions	Value			Units
			Min.	Typ.	Max.	
C_{iss}	Input Capacitance	$V_{GS} = 0V$	--	2062	--	pF
C_{oss}	Output Capacitance	$V_{DS} = 10V$	--	407	--	
C_{rss}	Reverse Transfer Capacitance	$f = 1.0MHz$	--	382	--	
R_G	Gate resistance	$V_{GS}=0V, V_{DS}=0V, f=1.0MHz$	--	2.6	--	Ω



Resistive Switching Characteristics						
Symbol	Parameter	Test Conditions	Value			Units
			Min.	Typ.	Max.	
$t_{d(ON)}$	Turn-on Delay Time	$I_D = 20A$	--	30	--	ns
t_r	Rise Time	$V_{DS} = 10V$	--	12	--	
$t_{d(OFF)}$	Turn-Off Delay Time	$V_{GS} = 4.5V$	--	35	--	
t_f	Fall Time	$R_G = 3.0\Omega$	--	21	--	
Q_g	Total Gate Charge	$V_{GS} = 10V$	--	63.1	--	nC
Q_{gs}	Gate Source Charge	$V_{DS} = 10V$	--	2.6	--	
Q_{gd}	Gate Drain Charge	$I_D = 8.0A$	--	13.6	--	



Source-Drain Diode Characteristics						
Symbol	Parameter	Test Conditions	Value			Units
			Min.	Typ.	Max.	
I_S	Diode Forward Current	$T_C = 25\text{ }^{\circ}\text{C}$	--	--	20	A
V_{SD}	Diode Forward Voltage	$I_S=20A, V_{GS}=0V$	--	--	1.2	V

a1: Repetitive rating; pulse width limited by maximum junction temperature

a2: $V_{DD}=10V, L=0.1mH, R_G=25\Omega$, Starting $T_J=25^{\circ}\text{C}$

a3: Surface Mounted on FR4 Board, $t \leq 10\text{sec}$

Characteristics Curve:













Figure 13: Max. Transient Thermal Impedance


Test Circuit & Waveform:

Figure 14: Gate Charge Test Circuit & Waveform

Figure 15: Resistive Switching Test Circuit & Waveforms

Figure 16: Unclamped Inductive Switching Test Circuit & Waveforms

Package Outline:


Symbol	Dimensions In Millimeters		
	Min	Ref	Max
A	1.350	1.550	1.750
A1	0.030	0.140	0.250
A2	1.350	1.450	1.550
b	0.330	0.430	0.530
c	0.160	0.205	0.250
D	4.700	5.000	5.300
E	3.800	3.900	4.000
E1	5.800	6.000	6.200
e	1.270(BSC)		
L	0.400	0.835	1.270
θ	0°	4°	8°

Revision History:

Revision	Date	Descriptions
Rev 1.1	July.2025	Initial Version

Disclaimer:

The information in this document is believed to be accurate and reliable. However, no responsibility is assumed by LW-Micro for its use. All operating parameters must be designed, validated and tested to ensure they meet the requirements of your application. LW-Micro reserves the right to make any specification and/or circuitry changes without prior notification. Before starting a brand-new project, please contact LW-Micro Sales to get the most recent relevant information.

Mailing Address: Unit 02&04&05, 10th Floor, Building 5, No.666 Shengxia Road, No.122 Yindong Road,
China (Shanghai) Pilot Free Trade Zone
Shanghai Lewa Micro-electronics Technology Co., Ltd