

1		2		3		4		5		6		7		8	
SAMZO		REAC/ROHS								REV	ECN NO	DESRIPTION	DESIGN	APPROVAL	DATE
										A1	NEW	Replace frame			2018.06.21
E															
D	P.1 3 1 ② 35±2mm 剥皮烫锡3mm ① ③ 端子刺破面朝上														
C															
B	P位配线图 P.1 红 1 黑 2 白 3 使用规格参数 1.线压入端子后不能有退PIN. 2.连接器方向要与图面一至. 3.注意产品尺寸需要在公差内. 4.禁止使用1级环境管理物质，具体物质参见客户要求. 5.测试条件:电压150V/0.01S, 导电阻抗:50hm, 绝缘阻抗:2M0hm. 6.线材与端子保持力:保持力为0.5公斤MIN拉力。														
A	ITEM	DESCRIPTION	MATERIAL	QTY	FINSH/COLOR						FIRST VIEW		The copyright belongs to samzo parts [China] Co., Ltd. please use the material after samzo parts agree to authorize. The final right of interpretation belongs to samzo parts. WWW.KKK-JP.COM		TITLE::
	1	线材	UL 10064 32AWG	3	0.38mm L=38mm									0.8刺破端子线-3P L=38mm	
	2	胶壳	0.8刺破式-3PIN	1	白色				GENERAL TOLERANCE					DWG NO: 08CC-P000	
	2	锡头	镀锡长度L=3mm	3					≥0~2<	±0.15	SCALE	1:1	UNIT	mm	PART NO: 08CC2403001
						DESIGN	WANGGUIFA	2018.06.12	≥2~5<	±0.25	SAMZO COMPONENTS Electronic switch and connector manufacturer			MODEL NO: A125B-3P-L38X3-P1	
						CHECKED	ZHENGUILAN	2018.06.12	≥0~2<	±0.15				NAME:	
						APPROVED	LILIANJIANG	2018.06.14	≥5	±0.35				TERMINAL WIRE CONNECTOR	
	1	2	3	4	5	6	7	8							