

6

5

4

3

2

1

D

D

C



C

B

B

A

A

 $\varnothing 3.60 [.142]$

22.00 [.866]

 $\varnothing 5.56 [.219]$ $\varnothing 4.78 [.188]$ **NOTES:**

- MATERIAL AND FINISHES:
CONTACT: PRECISION MACHINED COPPER ALLOY, GOLD FLASH OVER NICKEL PLATE.
RETENTION RING: POLYETHERIMIDE, COLOR: BLACK.
SPRING WAVE WASHER: BERYLLIUM COPPER, GOLD FLASH WITH NICKEL PLATE.
- DETAILED PRODUCT, MECHANICAL AND ELECTRICAL INFORMATION IS AVAILABLE IN THE LATEST COMBO-D PRODUCT PUBLICATION AT CONNECTPOSITRONIC.COM.
- CONTACT IS COMPLIANT TO THE CURRENT RoHS DIRECTIVE.

BY APG		CHK SS		3RD ANGLE 		POSITRONIC BELIEVES THE DATA ON THE DRAWING TO BE RELIABLE. THE USER EMPLOYS SUCH INFORMATION AT HIS OWN DISCRETION AND RISK. POSITRONIC ASSUMES NO RESPONSIBILITY FOR RESULTS OBTAINED OR DAMAGES INCURRED FROM USE OF SUCH INFORMATION IN WHOLE OR IN PART.  Positronic® CONNECTPOSITRONIC.COM			
APR PA		RELEASED DATE: 2019-08-30		SCALE NTS					
TOLERANCES						PART NUMBER MS4008D/AA		SERIES CBD/CBM	
±0.03mm [.001 INCHES]FOR MALE CONTACT MATING DIAMETERS ±0.08mm [.003 INCHES]FOR CONTACT TERMINATION DIAMETERS ±0.13mm [.005 INCHES]FOR ALL OTHER DIAMETERS ±0.38mm [.015 INCHES]FOR ALL OTHER DIMENSIONS ±5° FOR ALL ANGLES DIMENSION ARE IN MILLIMETERS [INCHES]						TITLE MS4008D/AA			
						CREATED ON: 2019-08-29		SHEET SHEET 1 OF 1	

6

5

4

3

2

1