



Precision Automotive Thin Film Chip Resistors, AEC-Q200 Qualified, 2 kV ESD Rating



These chip resistors are available in wraparound terminations styles in 8 case sizes. They incorporate self passivated enhanced tantalum nitride resistor film to give superior performance on moisture resistance, electrostatic discharge, voltage coefficient, power handling and resistance stability. The terminations consist of an adhesion layer, a leach resistant nickel barrier, and solder coating (lead (Pb)-free). This product will out-perform all requirements of AEC-Q200.

CONSTRUCTION



FEATURES

- Resistance range: 2.5 Ω to 3 M Ω
- AEC-Q200 qualified
- AEC-Q200 ESD rated class 1C (2 kV)
- Laser trimmed to any value
- Moisture resistant to MIL-STD-202, method 202
- Tantalum nitride resistor film on high purity alumina substrate
- 100 % visual inspected per MIL-PRF-55342
- Laser-trimmed tolerances to ± 0.1 %
- Load life stability < 0.05 % at 1000 h at 70 $^{\circ}$ C
- Very low noise and voltage coefficient (< -30 dB, < 0.1 ppm/V)
- Sulfur resistant (per ASTM B809-95 humid vapor test)
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912



RoHS
COMPLIANT
HALOGEN
FREE
GREEN
(5-2008)

TYPICAL PERFORMANCE


	ABSOLUTE
TCR	25
TOL.	0.1

STANDARD ELECTRICAL SPECIFICATIONS

TEST	SPECIFICATIONS	CONDITIONS
Material	Tantalum nitride	-
Resistance Range	2.5 Ω to 3 M Ω	-
TCR: Absolute	± 25 ppm/ $^{\circ}$ C to ± 100 ppm/ $^{\circ}$ C	-55 $^{\circ}$ C to +125 $^{\circ}$ C
Tolerance: Absolute	± 0.1 % to ± 1.0 %	+25 $^{\circ}$ C
Stability: Absolute	± 0.05 %	2000 h at 70 $^{\circ}$ C rated power
Stability: Ratio	Not applicable	-
Voltage Coefficient	Less than 0.1 ppm/V	-
Working Voltage	75 V to 200 V	-
Operating Temperature Range	-55 $^{\circ}$ C to +155 $^{\circ}$ C	-
Storage Temperature Range	-55 $^{\circ}$ C to +155 $^{\circ}$ C	-
Noise	< -30 dB	-
Shelf Life Stability: Absolute	100 ppm	1 year at 25 $^{\circ}$ C

COMPONENT RATINGS


CASE SIZE	POWER RATING (mW)	WORKING VOLTAGE (V)	RESISTANCE RANGE (Ω)
0402	50	75	20 to 51K
0603	150	75	2.5 to 130K
0805	200	100	10 to 301K
1206	400	200	10 to 1M
1505	400	150	10 to 1M
2208	750	150	10 to 1.75M
2010	800	200	10 to 2M
2512	1000	200	10 to 3M

DIMENSIONS in inches


CASE SIZE	L	W	T	D	E
0402	0.041 ± 0.003	0.022 ± 0.003	0.015 ± 0.003	0.010 ± 0.005	0.010 ± 0.005
0603	0.064 ± 0.006	0.032 ± 0.005	0.015 ± 0.003	0.012 ± 0.005	0.015 ± 0.005
0805	0.080 ± 0.006	0.050 ± 0.005	0.015 ± 0.003	0.015 ± 0.005	0.015 ± 0.005
1206	0.126 ± 0.008	0.063 ± 0.005	0.015 ± 0.003	0.020 ± 0.005 / - 0.010	0.020 ± 0.005 / - 0.010
1505	0.155 ± 0.007	0.050 ± 0.005	0.015 ± 0.003	0.015 ± 0.005	0.015 ± 0.005
2010	0.209 ± 0.009	0.098 ± 0.005	0.015 ± 0.003	0.020 ± 0.005	0.020 ± 0.005
2208	0.230 ± 0.007	0.075 ± 0.005	0.015 ± 0.003	0.020 ± 0.005	0.020 ± 0.005
2512	0.259 ± 0.009	0.124 ± 0.005	0.015 ± 0.003	0.020 ± 0.005	0.020 ± 0.005

ENVIRONMENTAL TESTS (Vishay Performance vs. AEC-Q200 Requirements)

ENVIRONMENTAL TEST	CONDITIONS	LIMITS PER AEC-Q200	TYPICAL VISHAY PERFORMANCE
Resistance Temperature Characteristic	-55 °C to +125 °C	± 50 ppm/°C	± 35 ppm/°C
Max. Ambient Temp. at Rated Wattage		+70 °C	+70 °C
Max. Ambient Temp. at Power Derating		+150 °C	+150 °C
High Temperature Storage ΔR	MIL-STD-202, 108, 1000 h at 125 °C	± 0.1 %	+ 0.016 %
Temperature Cycling ΔR	JESD22, JA-104, 1000 cycles, -55 °C to +125 °C	± 0.15 %	+ 0.013 %
Moisture Resistance ΔR	MIL-STD-202, 106	± 0.20 %	+ 0.0010 %
Biased Humidity ΔR	MIL-STD-202, 103, 1000 h at 85 °C, 85 % RH, 10 % P	± 0.10 %	+ 0.004 %
Life ΔR	MIL-STD-202, 108 at 125 °C, 1000 h	± 0.1 %	+ 0.0220 %
Mechanical Shock ΔR	MIL-STD-202, method 213, condition C	± 0.1 %	+ 0.004 %
Vibration ΔR	MIL-STD-202 method 204, 10 Hz to 2 kHz	± 0.1 %	+ 0.0030 %
Resistance to Soldering Heat ΔR	MIL-STD-202 method 210, condition D	± 0.10 %	+ 0.0150 %
Electrostatic Discharge ΔR	AEC-Q200-002 at 2 kV, human body	± 0.10 %	- 0.032 %
Solderability Visual	J-STD-002, method B and B1	95 %	Acceptable
Terminal Strength ΔR	AEC-Q200-006 at 1 kg for 60 s	± 0.10 %	+ 0.009 %
Flame Retardance Visual	AEC-Q200-001 para 4.0		Acceptable

DERATING CURVE


**GLOBAL PART NUMBER INFORMATION**

New Global Part Numbering: PAT1206E1002BST1

P	A	T	1	2	0	6	E	1	0	0	2	B	S	T	1
GLOBAL MODEL	CASE SIZE	TCR CHARACTERISTIC		RESISTANCE				TOLERANCE		TERMINATION		PACKAGING			
PAT	0402 0603 0805 1206 1505 2010 2208 2512	E = ± 25 ppm/°C H = ± 50 ppm/°C K = ± 100 ppm/°C L = ± 200 ppm/°C	The first 3 digits are significant figures and the last digit specifies the number of zeros to follow. "R" designates the decimal point. Example: 10R0 = 10 Ω 1000 = 100 Ω 1002 = 10 kΩ				B = ± 0.1 % D = ± 0.5 % F = ± 1.0 % G = ± 2.0 % J = ± 5.0 %		S = wraparound lead (Pb)-free solder w/nickel barrier		TAPE AND REEL T1 = 1000 min., 1000 mult ⁽¹⁾ TF = full reel TS = 100 min., 1 mult				

Note⁽¹⁾ Preferred packaging code

RESISTANCE	TCR (ppm/$^{\circ}$C)	TOLERANCE (%)
10 Ω to 1 M Ω	25, 50, 100, 200	0.1, 0.5, 1, 2, 5
5 Ω to 10 Ω	100, 200	1, 2, 5
1.0 Ω to 5 Ω	200	1, 2, 5



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Vishay:

<u>PAT0805E25R0BST1</u>	<u>PAT1206E20R0BST1</u>	<u>PAT1206E49R9BST1</u>	<u>PAT0603E1001BST1</u>	<u>PAT0603E1002BST1</u>
<u>PAT0603E1152BST1</u>	<u>PAT0603E1332BST1</u>	<u>PAT0603E1472BST1</u>	<u>PAT0603E1501BST1</u>	<u>PAT0603E1621BST1</u>
<u>PAT0603E1780BST1</u>	<u>PAT0603E1781BST1</u>	<u>PAT0603E2000BST1</u>	<u>PAT0603E2001BST1</u>	<u>PAT0603E2002BST1</u>
<u>PAT0603E2431BST1</u>	<u>PAT0603E2490BST1</u>	<u>PAT0603E24R9BST1</u>	<u>PAT0603E3011BST1</u>	<u>PAT0603E3012BST1</u>
<u>PAT0603E3162BST1</u>	<u>PAT0603E3482BST1</u>	<u>PAT0603E4000BST1</u>	<u>PAT0603E4002BST1</u>	<u>PAT0603E4422BST1</u>
<u>PAT0603E4702BST1</u>	<u>PAT0603E4751BST1</u>	<u>PAT0603E4990BST1</u>	<u>PAT0603E4992BST1</u>	<u>PAT0603E5112BST1</u>
<u>PAT0603E6042BST1</u>	<u>PAT0603E6121BST1</u>	<u>PAT0603E6190BST1</u>	<u>PAT0603E6652BST1</u>	<u>PAT0603E7501BST1</u>
<u>PAT0603E7502BST1</u>	<u>PAT0603E9090BST1</u>	<u>PAT0603E90R9BST1</u>	<u>PAT0805E1001BST1</u>	<u>PAT0805E1002BST1</u>
<u>PAT0805E1003BST1</u>	<u>PAT0805E10R0BST1</u>	<u>PAT0805E1102BST1</u>	<u>PAT0805E1103BST1</u>	<u>PAT0805E1152BST1</u>
<u>PAT0805E1211BST1</u>	<u>PAT0805E1241BST1</u>	<u>PAT0805E1270BST1</u>	<u>PAT0805E1500BST1</u>	<u>PAT0805E1503BST1</u>
<u>PAT0805E1802BST1</u>	<u>PAT0805E1912BST1</u>	<u>PAT0805E2001BST1</u>	<u>PAT0805E2202BST1</u>	<u>PAT0805E2431BST1</u>
<u>PAT0805E2493BST1</u>	<u>PAT0805E2612BST1</u>	<u>PAT0805E3010BST1</u>	<u>PAT0805E3012BST1</u>	<u>PAT0805E3090BST1</u>
<u>PAT0805E3791BST1</u>	<u>PAT0805E4022BST1</u>	<u>PAT0805E4371BST1</u>	<u>PAT0805E4701BST1</u>	<u>PAT0805E4990BST1</u>
<u>PAT0805E4992BST1</u>	<u>PAT0805E49R9BST1</u>	<u>PAT0805E5621BST1</u>	<u>PAT0805E5902BST1</u>	<u>PAT0805E6041BST1</u>
<u>PAT0805E6341BST1</u>	<u>PAT0805E6982BST1</u>	<u>PAT0805E7151BST1</u>	<u>PAT0805E8982BST1</u>	<u>PAT1206E1001BST1</u>
<u>PAT1206E1002BST1</u>	<u>PAT1206E1003BST1</u>	<u>PAT1206E1022BST1</u>	<u>PAT1206E10R0BST1</u>	<u>PAT1206E1103BST1</u>
<u>PAT1206E1502BST1</u>	<u>PAT1206E1503BST1</u>	<u>PAT1206E1692BST1</u>	<u>PAT1206E1741BST1</u>	<u>PAT1206E1961BST1</u>
<u>PAT1206E2001BST1</u>	<u>PAT1206E2002BST1</u>	<u>PAT1206E2003BST1</u>	<u>PAT1206E2491BST1</u>	<u>PAT1206E2493BST1</u>
<u>PAT1206E2742BST1</u>	<u>PAT1206E2802BST1</u>	<u>PAT1206E2940BST1</u>	<u>PAT1206E3011BST1</u>	<u>PAT1206E3012BST1</u>
<u>PAT1206E30R1BST1</u>	<u>PAT1206E3651BST1</u>	<u>PAT1206E4021BST1</u>	<u>PAT1206E4022BST1</u>	<u>PAT1206E4222BST1</u>