



Female Disconnects – Nylon Insulated with Insulation Grip Bullet Style


Product Number†	UPC (054007-)	Wire Range (AWG)	Mating Snap Diameter S	L	Barrel Length	Barrel I.D.	Maximum Insulation Diameter	Terminals per: Carton Case	
MNG18-156DFIK	01305	22-18	0.156	1.02	0.25	0.095	0.145	—	1000
MNG18-180DFIK	02254	22-18	0.180	1.02	0.25	0.095	0.145	—	1000
MNG18-180DFIK	02254	22-18	0.180	1.02	0.25	0.095	0.145	—	1000
MNG14-156DFIX	11712	16-14	0.156	1.02	0.25	0.115	0.170	100	500
MNG14-156DFIK	01782	16-14	0.156	1.02	0.25	0.115	0.170	—	1000
MNG14-180DFIX	11713	16-14	0.180	1.02	0.25	0.115	0.170	100	500
MNG14-180DFIK	02268	16-14	0.180	1.02	0.25	0.115	0.170	—	1000




MNG18-156DFI
22-18
MNG18-156DM



MNG18-180DFI
22-18
MNG18-180DM



MNG14-156DFI
16-14
MNG14-156DM



MNG14-180DFI
16-14
MNG14-180DM

Wire Range
Suggested Mate