


FCA - 410 - 1624M Product Details



FCA - 410 - 1624M

(M83536/16 - 024M)

 [Active](#)

Military/Aerospace Mid - Range Relays

[Not EU RoHS or ELV Compliant](#)

Product Highlights:

- ? FCA 10 - 25 Amp Relay Series
- ? DC Actuating System
- ? Coil Voltage = 28 VDC
- ? Contact Arrangement = 4 Form C, 4PDT, 4 C/O
- ? Current Rating = 10 Amps.

[View all Features](#) | [Find Similar Products](#)

Quick Links

[Check Pricing & Availability](#)

[Search for Tooling](#)

[Product Feature Selector](#)

[Contact Us About This Product](#)

Documentation & Additional Information

Product Drawings:

- ? [MSD RELAY](#) (PDF, English)

Catalog Pages/Data Sheets:

- ? None Available

Product Specifications:

- ? None Available

Application Specifications:

- ? None Available

Instruction Sheets:

- ? None Available

CAD Files:

- ? None Available

Additional Information:

- ? [Product Line Information](#)

Related Products:

- ? [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- ? [Terminal Type](#) = Solder Hook

Electrical Characteristics:

- ? [Actuating System](#) = DC
- ? [Coil Voltage \(VDC\)](#) = 28
- ? [Current Rating \(Amps.\)](#) = 10

Termination Related Features:

- ? [Terminal Plating](#) = Tin -Lead
- ? Auxiliary Contacts = Without

Body Related Features:

- ? Series = FCA 10 - 25 Amp Relay
- ? [Mount Type](#) = Side Mount

Configuration Related Features:

- ? [Contact Arrangement](#) = 4 Form C, 4PDT, 4 C/O
- ? [Coil Suppression Diode](#) = With
- ? Coil Magnetic System = Polarized, Monostable

Industry Standards:

- ? Government/Industry Qualification = No
- ? Government/Industry Part Number = M83536/16 - 024M
- ? [RoHS/ELV Compliance](#) = Not ELV/RoHS compliant
- ? [Lead Free Solder Processes](#) = Not suitable for lead free processing

Other:

- ? Brand = CII