


# Shielded Power Inductors – SER1052



- High current, low DCR shielded power inductors
- 10.2 × 11 mm base; only 5.2 mm tall

**Designer's Kit C421** contains 3 of each value

**Core and winding loss** See [www.coilcraft.com/coreloss](http://www.coilcraft.com/coreloss)

**Core material** Ferrite

**Terminations** RoHS compliant tin-silver over tin over nickel over phos bronze (pins 1 and 2); matte tin over nickel over phos bronze (pin 3). Other terminations available at additional cost.

**Weight** 1.6 g

**Ambient temperature** -40°C to +85°C with (40°C rise) Irms current.

**Maximum part temperature** +125°C (ambient + temp rise). [Derating](#).

**Storage temperature** Component: -40°C to +125°C.

Tape and reel packaging: -40°C to +80°C

**Resistance to soldering heat** Max three 40 second reflows at +260°C, parts cooled to room temperature between cycles

**Moisture Sensitivity Level (MSL)** 1 (unlimited floor life at <30°C / 85% relative humidity)

**Failures in Time (FIT) / Mean Time Between Failures (MTBF)**

38 per billion hours / 26,315,789 hours, calculated per Telcordia SR-332

**Packaging** 200/7" reel; 700/13" reel Plastic tape: 24 mm wide, 0.4 mm thick, 16 mm pocket spacing, 5.45 mm pocket depth

**PCB washing** Tested to MIL-STD-202 Method 215 plus an additional aqueous wash. See [Doc787\\_PCB\\_Washing.pdf](#).

| Part number <sup>1</sup> | Inductance<br>±20% <sup>2</sup><br>(μH) | DCR<br>max <sup>3</sup><br>(mOhm) | SRF<br>typ <sup>4</sup><br>(MHz) | Isat (A) <sup>5</sup> |             |             | Irms(A) <sup>6</sup> |              |
|--------------------------|-----------------------------------------|-----------------------------------|----------------------------------|-----------------------|-------------|-------------|----------------------|--------------|
|                          |                                         |                                   |                                  | 10%<br>drop           | 20%<br>drop | 30%<br>drop | 20°C<br>rise         | 40°C<br>rise |
| SER1052-801ML_           | 0.80                                    | 4.0                               | 100                              | 24.9                  | 25.2        | 25.6        | 12.5                 | 16.3         |
| SER1052-102ML_           | 1.0                                     | 4.0                               | 95                               | 16.5                  | 17.0        | 17.5        | 12.5                 | 16.3         |
| SER1052-122ML_           | 1.2                                     | 6.0                               | 91                               | 20.5                  | 21.0        | 21.3        | 11.0                 | 15.0         |
| SER1052-132ML_           | 1.3                                     | 4.0                               | 81                               | 12.9                  | 16.8        | 17.2        | 12.5                 | 16.3         |
| SER1052-152ML_           | 1.5                                     | 4.0                               | 75                               | 13.5                  | 14.0        | 14.5        | 11.0                 | 15.0         |
| SER1052-182ML_           | 1.8                                     | 6.0                               | 70                               | 13.3                  | 13.8        | 14.3        | 11.0                 | 15.0         |
| SER1052-202ML_           | 2.0                                     | 9.0                               | 65                               | 15.3                  | 15.8        | 16.2        | 8.5                  | 11.5         |
| SER1052-222ML_           | 2.2                                     | 4.0                               | 58                               | 8.9                   | 9.6         | 10.0        | 12.5                 | 16.3         |
| SER1052-252ML_           | 2.5                                     | 7.5                               | 55                               | 11.4                  | 11.8        | 12.1        | 9.0                  | 12.0         |
| SER1052-322ML_           | 3.2                                     | 6.0                               | 53                               | 7.3                   | 7.8         | 8.5         | 11.0                 | 15.0         |
| SER1052-402ML_           | 4.0                                     | 9.0                               | 47                               | 8.3                   | 8.5         | 8.8         | 8.5                  | 11.5         |
| SER1052-432ML_           | 4.3                                     | 7.5                               | 44                               | 6.4                   | 6.8         | 7.0         | 9.0                  | 12.0         |
| SER1052-572ML_           | 5.7                                     | 9.0                               | 35                               | 5.4                   | 5.8         | 6.0         | 8.5                  | 11.5         |

1. Please specify **termination** and **packaging** codes:

## SER1052-572MLD

**Termination:** L = RoHS compliant tin-silver over copper (pins 1 and 2); matte tin over nickel over phos bronze (pin 3).

Special order:

**T** = RoHS tin-silver-copper (95.5/4/0.5) or **S** = non-RoHS tin-lead (63/37).

**Packaging:** C = 7" machine-ready reel. EIA-481 embossed plastic tape (200 parts per full reel).

**B** = Less than full reel. In tape, but not machine ready.  
To have a leader and trailer added (\$25 charge), use code letter C instead.

**D** = 13" machine-ready reel. EIA-481 embossed plastic tape. Factory order only, not stocked (700 parts per full reel)

- Inductance measured at 100 kHz, 0.1 Vrms, 0 Adc on an Agilent/HP 4284A or equivalent.
- DCR measured on a micro-ohmmeter.
- SRF measured using an Agilent/HP 4395A network analyzer and an Agilent/HP 16193A test fixture.
- DC current at 25°C that causes the specified inductance drop from its value without current.  
[Click for temperature derating information.](#)
- Current that causes the specified temperature rise from 25°C ambient. This information is for reference only and does not represent absolute maximum ratings.  
[Click for temperature derating information.](#)
- Electrical specifications at 25°C.  
Refer to Doc 362 "Soldering Surface Mount Components" before soldering.



[www.coilcraft.com](http://www.coilcraft.com)

**US** +1-847-639-6400 [sales@coilcraft.com](mailto:sales@coilcraft.com)  
**UK** +44-1236-730595 [sales@coilcraft-europe.com](mailto:sales@coilcraft-europe.com)  
**Taiwan** +886-2-2264 3646 [sales@coilcraft.com.tw](mailto:sales@coilcraft.com.tw)  
**China** +86-21-6218 8074 [sales@coilcraft.com.cn](mailto:sales@coilcraft.com.cn)  
**Singapore** + 65-6484 8412 [sales@coilcraft.com.sg](mailto:sales@coilcraft.com.sg)

Document 535-1 Revised 09/09/15


© Coilcraft Inc. 2017

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.




# Shielded Power Inductors - SER1052 Series




## Typical L vs Frequency



## Typical L vs Current



Prior to 2012, parts may have been marked differently



Dimensions are in inches  
mm

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Coilcraft:

[SER1052-202MLC](#) [SER1052-432MLB](#) [SER1052-122MLB](#) [SER1052-132MLB](#) [SER1052-222MLB](#) [SER1052-322MLB](#) [SER1052-572MLB](#) [SER1052-202MLB](#) [SER1052-402MLC](#) [SER1052-432MLC](#) [SER1052-132MLC](#) [SER1052-222MLC](#) [SER1052-252MLB](#) [SER1052-801MLC](#) [SER1052-152MLC](#) [SER1052-152MLB](#) [SER1052-182MLC](#) [SER1052-102MLC](#) [SER1052-102MLB](#) [SER1052-801MLB](#) [SER1052-182MLB](#) [SER1052-122MLC](#) [SER1052-402MLB](#) [SER1052-572MLC](#) [SER1052-252MLC](#) [SER1052-322MLC](#)