

Part Number: 16020083

Product Description: SL Crimp Terminal, Series 70058, Female, 30-24 AWG, with 0.76µm Selective Gold (Au) Plated Contact,

Reel

Status: Active

**Engineering Number:** 70058-0008

Series Number: 70058

Product Category: Crimp Terminals
Packaging Alternative: 16020098 (Bag)

#### **Documents & Resources**

#### **Drawings**

Drawing 016020083\_sd.pdf

#### **Specifications**

Product Specification PS-70058-001.pdf Product Specification PS-70400-001.pdf Test Summary TS-70058-001-001.pdf

### **Product Environment Compliance**

#### Compliance

GADSL/IMDS	Compliant with Exemption 44; 34; 33
China RoHS	<b>©</b>
EU ELV	Compliant per 2000/53/EC
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant per EU 2015/863

#### **Multiple Part Product Compliance Statements**

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474

## **Part Details**

## General

Status	Active
Category	Crimp Terminals
Series	70058
Description	SL Crimp Terminal, Series 70058, Female, 30-24 AWG, with 0.76µm Selective Gold (Au) Plated Contact, Reel
Application	Signal, Wire-to-Board
Product Family	SL Modular Connectors
Product Name	CyClone,EXTreme Ten60Power,SL
UPC	800753749139

## Physical

Gender	Female
Material - Metal	Phosphor Bronze
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Net Weight	0.073/g
Packaging Type	Reel
Plating min - Mating	0.762µm
Plating min - Termination	1.270µm
Termination Interface Style	Crimp or Compression
Wire Insulation Diameter	1.52mm max.
Wire Size (AWG)	24, 26, 28, 30
Wire Size mm <sup>2</sup>	N/A

## Solder Process Data

Lead-Free Process Capability   N/A	Lead-Free Process Capability	N/A	
------------------------------------	------------------------------	-----	--

## Use with Part(s)

Description	Part Number
SL Single Row Crimp Housings and CPA Retainers	<u>70066</u>
SL Dual Row Crimp Housings	<u>70450</u>
EXTreme Ten60Power Wire-to- Board Receptacle Housings	<u>172510</u>
EXTreme Ten60Power Panel-to- Board Receptacle Housings	<u>172512</u>

# **Application Tooling**

## Global

Description	Part Number
Insertion Tool for 70021,70028, 70110, 71851 Terminals / Extraction Tool for 91821 Terminals	11020022
Extraction Tool for SL Terminals, 36-22 AWG	<u>11030036</u>
Hand Crimp Tool for SL Crimp Terminals, 30-24 AWG	2002187000
FineAdjust Applicator for SL Female Crimp Terminal, Insulation OD 0.63-1.00mm, 30-24 AWG Wire	<u>639001500</u>
FineAdjust Applicator for SL Female Crimp Terminal, Insulation OD 1.01-1.52mm, 30-24 AWG Wire	639003100
T2 Terminator Tooling Die	639103100

# **Application Tooling**

## Japan

Description	Part Number
Hand Insertion Tool	570336000

This document was generated on Sep 15, 2024