

► [Heatsinks f.cool](#)

► [Cases f.case](#)

▼ [Connectors f.con](#)

► [Sockets](#)

▼ [PCB connectors](#)

■ [Male headers](#)

■ [Female headers](#)

■ [Direct female connectors](#)

■ [Jumpers](#)

► [IDC-connectors](#)

► [D-Sub connectors](#)

■ [Brackets for PC](#)

► [Optoelectronics](#)

Male headers

SL 2 ... / SL 22 ...

SL 22 190 72 S

two rows,  $\square$  0.635 mm

add to request



Features

Technical Drawing

Variants

Service

Accessories / related products

Article 1-10 of 17

1 | 2 > >>

Number per page: 10

Picture

Name



► **Female headers / BL 2 ...**  
Stamped contact spring (fork contact), for  $\square$  0...



► **Female headers / BL 4 ...**  
Stamped contact spring (fork contact), for  $\square$  0...



► **Female headers / BL LP 2 ...**  
for  $\square$  0.635 mm



► **Female headers / BL LP 4 ...**  
for square 0.635 mm, packing in a bar magazine (min. 4 contacts)



► **Female headers / BL 12 ...**  
for  $\square$  0.635 mm, can be put through from above and below



► **Female headers / BL 21 ...**  
 $\square$  0.635 mm, can be put through from above



► **Female headers / BL 6 ...**  
for  $\square$  0.635 mm and up to 0.85 mm  $\varnothing$



► **Female headers / BL 8 ...**  
for  $\square$  0.635 mm and up to 0.85 mm  $\varnothing$ , packing (option) bar magazine



► **Female headers / MK 221 ...**  
 $\square$  0.635 mm and up to 0.85 mm  $\varnothing$ ; No capillary action when soldering due to protected contact insert...



► **Female headers / BL 10 ...**  
 $\square$  0.635 mm and up to 0.85 mm  $\varnothing$ , with aligned contact pin

Article 1-10 of 17

1 | 2 > >>