



Descriptions

The SGM2576YN5G/TR is a small, single channel load switch using P-Channel MOSFET for minimum power loss. Advanced gate control design supports operating voltages as low as 1.5V with minimal increase in ON-Resistance and power loss. It is designed for load switching applications with ultra-low quiescent current (0.5uA) and ultra-low standby current (150nA).

The SGM2576YN5G/TR offers industry leading True Reverse Current Blocking performance. It minimizes reverse current flow in the event that the VOUT pin voltage exceeds the VIN voltage. The device is controlled by external logic pin, allowing optimization of battery life, and portable device autonomy.

The SGM2576YN5G/TR is available in SOT-23-5L package. Standard products are Pb-free and Halogen-free.

Features

- Input Voltage Range : 1.5V~5.5V
- Main switch Ron : 32mΩ (VIN=5.5V Typ.)
- Quiescent current : 0.4uA
- Standby current : 80nA
- Maximum Output current : 2A
- Reverse Current Blocking (RCB)
- Controlled Rise Time: 570us at 3.3VIN
- Quick Output Discharge (QOD) : 85Ω(Typ.)
- Compact package: SOT-23-5L

Applications

- Wearables
- Smartphones
- Tablets
- Portable Speakers

Order Information

Part Number	Package		Quantity per Reel
SGM2576YN5G/TR	SOT-23-5L	Tape and Reel	3,000PCS



Pin Information




Fig. 1 Pin Information (Top View)

Pin	Symbol	Description
1	VOUT	Output pin
2	GND	Ground
3	NC	Not Connection
4	EN	Enable (Active high)
5	VIN	Input pin

Block Diagram




Fig. 2 Block Diagram



Typical Applications




Fig. 3 Typical Applications

Absolute Maximum Ratings

The absolute maximum ratings are stress ratings only. Stresses exceeding the range in Table 3 might cause substantial damage to the device. Functional operation of the device under other conditions is not implied. Prolonged exposure to extreme conditions might affect device reliability.

Parameter	Symbol	Condition	Min.	Max.	Unit
Input voltage	V_{IN}		-0.3	6	V
Output voltage	V_{OUT}		-0.3	6	V
Enable voltage	V_{EN}		-0.3	6	V
Maximum continuous switch current	I_{MAX}			2	A
Maximum junction temperature	$T_{J,MAX}$			125	°C
Lead Temperature	T_{LEAD}	Soldering, 10 sec.		300	°C
Storage Temperature Range	T_{STG}		-65	150	°C
Human Body Model, JESD22-A114	HBM		4000		V
Charged Device Model, JESD22-C101	CDM		2000		V
MSL			Level 1		

Thermal Information

Parameter	Symbol	Value	Unit
Junction-to-Ambient thermal resistance*1	$R_{\theta JA}$		°C/W

*1: Surface mounted on FR-4 Board using 2 oz, 4 layer board, PCB board size is 3*3 square inches

Recommended Operation Conditions

Parameter	Symbol	Min.	Typ.	Max.	Unit
Input Voltage	V_{IN}	1.5		5.5	V
Enable voltage	V_{EN}	0		5.5	V
Output voltage	V_{OUT}	0		5.5	V
Operating Junction Temperature	T_J	-40		125	°C
Operating Ambient Temperature	T_A	-40		85	°C



Electrical Characteristics (Ta=25°C, VIN=3.3V unless otherwise noted)

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Units
IQ	Quiescent Current (1)	EN = Enable, IOUT=0 mA, VIN = VEN =5.5 V		0.4		uA
		EN=Enable, IOUT=0 mA, VIN=VEN=5.5 V, Ta=85 °C		0.7		
ISD	Shut Down Current	EN = Disable, IOUT=0 mA, VIN=1.5 V		65		nA
		EN = Disable, IOUT=0 mA, VIN=3.3 V		70		
		EN = Disable, IOUT=0 mA, VIN=4.2 V		75		
		EN = Disable, IOUT=0 mA, VIN=5.5 V		80		
		EN = Disable, IOUT=0 mA, VIN=5.5 V, Ta=55 °C (5)		140		
RON	On-Resistance	VIN=5.5 V, IOUT= 500 mA	Ta=25 °C	80		mΩ
			Ta=85 °C (5)	85		
		VIN=3.3 V, IOUT= 500 mA	Ta=25 °C	90		
			Ta=85 °C (5)	96		
		VIN=1.8 V, IOUT= 300 mA	Ta=25 °C (5)	100		
		VIN=1.5 V, IOUT= 100 mA	Ta=25 °C	120		
RDSC	Output Discharge Resistance	EN=Low , IFORCE= 10 mA		85		Ω
VIH	EN Input	VIN=1.5-5.5 V	1.2			V
VIL	Logic High Voltage	VIN=1.5-5.5 V			0.4	V
REN	EN pull down resistance	Internal Resistance		10		MΩ
IEN	EN Current	EN=VIN or GND		0.5		uA
VRCB_TH	RCB Protection Threshold Voltage	VOUT – VIN		39		mV
VRCB_RL	RCB Protection Release Voltage	VIN – VOUT		30		mV
tON	Turn-On Delay (2)	RL=150 Ω, COUT=0.1 μF		430		us
tR	VOUT Rise Time (2)			570		
tOFF	Turn-Off Delay (3), (5)	RL=150 Ω, COUT=0.1 μF		17		us
tF	VOUT Rise Time (3), (5)			15		

- Notes:
1. IQ does NOT include Enable pull down current through the pull down resistor RPD.
 2. tON = tON + tR
 3. tOFF = tOFF + tF
 4. Output discharge path is enabled during off.
 5. By design; characterized, not production tested.



Timing Diagram






Fig. 6 Timing Diagram


Typical characteristics ($T_a=25^\circ\text{C}$, $V_{IN}=5\text{V}$, $I_{OUT}=500\text{mA}$, $C_{IN}=1\mu\text{F}$, $C_{OUT}=0.1\mu\text{F}$, unless otherwise noted)




R_{ON} vs. Load current ($V_{EN}=H$)




R_{ON} vs. V_{IN} ($V_{EN}=V_{IN}$, $I_{LOAD}=200\text{mA}$)



Standby current vs. V_{IN} (V_{OUT} =OPEN)



Standby current vs. V_{IN} (V_{OUT} =GND)




Quiescent current vs. V_{IN} (V_{EN} =H, NO LOAD)



Turn on transient ($C_{in}=1\mu F, C_{out}=0.1\mu F, R_{LOAD}=150\Omega, V_{IN}=3.3V$)





Turn off transient ($C_{in}=1\mu F, C_{out}=0.1\mu F, R_{LOAD}=150\Omega, V_{IN}=3.3V$)







Package Outline Dimensions

SOT-23-5L



RECOMMENDED LAND PATTERN (Unit: mm)



Symbol	Dimension in Millimeters		
	Min.	Typ.	Max.
A	-	-	1.30
A1	0.03	-	0.15
A2	1.05	1.10	1.15
b	0.28	-	0.45
c	0.12	-	0.23
D	2.82	2.92	3.02
E	1.50	1.60	1.70
E1	2.60	2.80	3.00
e	0.95BSC		
e1	1.90BSC		
L	0.35	-	0.55
θ	0°	-	8°



Attention

- Any and all HUA XUAN YANG ELECTRONICS products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your HUA XUAN YANG ELECTRONICS representative nearest you before using any HUA XUAN YANG ELECTRONICS products described or contained herein in such applications.
- HUA XUAN YANG ELECTRONICS assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein.
- Specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.
- HUA XUAN YANG ELECTRONICS CO.,LTD. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could give rise to accidents or events that could endanger human lives, that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.
- In the event that any or all HUA XUAN YANG ELECTRONICS products(including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.
- No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of HUA XUAN YANG ELECTRONICS CO.,LTD.
- Information (including circuit diagrams and circuit parameters) herein is for example only ; it is not guaranteed for volume production. HUA XUAN YANG ELECTRONICS believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.
- Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the HUA XUAN YANG ELECTRONICS product that you intend to use.