


**MODEL:** CPT-1255C-090 | **DESCRIPTION:** PIEZO BUZZER TRANSDUCER**FEATURES**

- externally driven
- wave solderable
- through hole


**SPECIFICATIONS**

| parameter              | conditions/description                 | min   | typ    | max    | units |
|------------------------|----------------------------------------|-------|--------|--------|-------|
| operating voltage      |                                        | 1     |        | 20     | Vp-p  |
| current consumption    | at 9 Vp-p, 4,000 Hz square wave        |       |        | 7      | mA    |
| rated frequency        |                                        |       | 4,000  |        | Hz    |
| sound pressure level   | at 10 cm, 3 Vp-p, 4,000 Hz square wave | 70    |        |        | dB    |
|                        | at 10 cm, 9 Vp-p, 4,000 Hz square wave | 85    |        |        | dB    |
| electrostatic capacity | at 120 Hz/1 V                          | 8,400 | 12,000 | 15,600 | pF    |
| dimensions             | Ø12.0 x 5.5                            |       |        |        | mm    |
| weight                 |                                        |       |        | 1.5    | g     |
| material               | PBT                                    |       |        |        |       |
| terminal               | pin type [Sn plating]                  |       |        |        |       |
| operating temperature  |                                        | -40   |        | 85     | °C    |
| storage temperature    |                                        | -40   |        | 85     | °C    |
| RoHS                   | yes                                    |       |        |        |       |

Notes: 1. All specifications measured at 5-35°C, humidity at 45-85%, under 86-106 kPa pressure, unless otherwise noted.


**SOLDERABILITY**

| parameter      | conditions/description                 | min | typ | max | units |
|----------------|----------------------------------------|-----|-----|-----|-------|
| wave soldering | see recommended wave soldering profile |     |     | 250 | °C    |




## MECHANICAL DRAWING

units: mm  
tolerance:  $\pm 0.5$  mm



## FREQUENCY RESPONSE CURVE



## PACKAGING


units: mm

Tray Size: 184 x 180 x 23 mm

Carton Size: 440 x 400 x 310 mm


Tray QTY: 100 pcs per tray

Carton QTY: 6,000 pcs per carton



|           |                                                                                     |
|-----------|-------------------------------------------------------------------------------------|
| Lot No.   | XXXXXXXXXX                                                                          |
| Model No. | XXXXXXXXXX                                                                          |
| Quantity. | XXXX Pcs                                                                            |
| Date:     |                                                                                     |
|           | DD MM YY                                                                            |
|           | MADE IN CHINA                                                                       |
|           |  |

The label is placed on the inner boxes and outer carton.



REVISION HISTORY

| rev. | description                       | date       |
|------|-----------------------------------|------------|
| 1.0  | initial release                   | 03/29/2016 |
| 1.01 | updated temperature rating        | 04/08/2019 |
| 1.02 | brand update                      | 11/22/2019 |
| 1.03 | logo, datasheet style update      | 08/05/2022 |
| 1.04 | changed to laser etching          | 05/13/2024 |
| 1.05 | CUI Devices rebranded to Same Sky | 09/11/2024 |

The revision history provided is for informational purposes only and is believed to be accurate.



Same Sky offers a one (1) year limited warranty. Complete warranty information is listed on our website.

Same Sky reserves the right to make changes to the product at any time without notice. Information provided by Same Sky is believed to be accurate and reliable. However, no responsibility is assumed by Same Sky for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

Same Sky products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

**sameskydevices.com**