



Connectors > Automotive Connectors > Automotive Connector Accessories > Automotive Connector Locks & Position Assurance



Connector & Contact Retention Accessory Type: **Secondary Lock**  
Primary Product Color: **White**  
Primary Product Material: **PBT GF**  
Operating Temperature Range: **-40 – 140 °C [-40 – 284 °F]**

Features

Product Type Features

Connector & Contact Retention Accessory Type	Secondary Lock
--	----------------

Body Features

Primary Product Color	White
Primary Product Material	PBT GF

Usage Conditions

Operating Temperature Range	-40 – 140 °C[-40 – 284 °F]
-----------------------------	----------------------------

Industry Standards

UL Flammability Rating	UL 94HB
------------------------	---------

Packaging Features

Packaging Quantity	2500
Packaging Method	Box

Other

Serviceable	Yes
-------------	-----

Product Compliance



For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts


TE Part # 1801263-1  
30POS MIXED MQS REC SEALED  
COD A

TE Part # 1801269-1  
COVER ASSY, 30 WAY HYBRID  
CONNECTOR


TE Part # 1801269-2  
COVER ASSY, 30 WAY HYBRID  
CONNECTOR

Customers Also Bought







TE Part #1415390-1  
PE014F03




TE Part #5-1462037-3  
IM41TS=IM RELAY 100mW 3V BIS




TE Part #1-1564559-1  
4POS, MCON 1.2 LL TAB SEALED  
COD A




TE Part #1456983-1  
1X4 FEM UNSEALED LOW PROFILE,  
KEY A




TE Part #1241414-1  
AMP MCP, RECEPTACLE AND TAB




TE Part #1670146-1  
MCON 1.2 CB REC SWS SN



TE Part #5-1579007-3  
EXTRACTION TOOL



TE Part #2301724-5  
16POS,060 SERIES,REC HSG,UNSLD



TE Part #1452839-5  
24 POS FEMALE HSG ASSY

Documents

Product Drawings  
SECONDARY LOCKING, 30 WAY  
English

CAD Files  
3D PDF  
3D  
Customer View Model  
ENG\_CVM\_CVM\_1801268-1\_A.2d\_dxf.zip  
English  
Customer View Model  
ENG\_CVM\_CVM\_1801268-1\_A.3d\_igs.zip  
English  
Customer View Model  
ENG\_CVM\_CVM\_1801268-1\_A.3d\_stp.zip  
English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Product Specifications



Product Specification

English