




Part No	Pin	A	B	C
WAFER-SH1.0-2PJK	2	1.00	5.00	2.40
WAFER-SH1.0-3PJK	3	2.00	6.00	3.40
WAFER-SH1.0-4PJK	4	3.00	7.00	4.40
WAFER-SH1.0-5PJK	5	4.00	8.00	5.40
WAFER-SH1.0-6PJK	6	5.00	9.00	6.40
WAFER-SH1.0-7PJK	7	6.00	10.00	7.40
WAFER-SH1.0-8PJK	8	7.00	11.00	8.40
WAFER-SH1.0-9PJK	9	8.00	12.00	9.40
WAFER-SH1.0-10PJK	10	9.00	13.00	10.40
WAFER-SH1.0-11PJK	11	10.00	14.00	11.40
WAFER-SH1.0-12PJK	12	11.00	15.00	12.40
WAFER-SH1.0-13PJK	13	12.00	16.00	13.40
WAFER-SH1.0-14PJK	14	13.00	17.00	14.40
WAFER-SH1.0-15PJK	15	14.00	18.00	15.40
WAFER-SH1.0-16PJK	16	15.00	19.00	16.40
WAFER-SH1.0-17PJK	17	16.00	20.00	17.40
WAFER-SH1.0-18PJK	18	17.00	21.00	18.40
WAFER-SH1.0-19PJK	19	18.00	22.00	19.40
WAFER-SH1.0-20PJK	20	19.00	23.00	20.40

技术要求Specification:

- 1、材质Material: PA66 UL94V-0;
- 2、塑件表面平整光洁, 无明显的毛刺、气泡、变形、浇口拉伤、缺料等不良现象。

Plastic surface smooth and clean, no obvious burrs, bubbles, distortion, gate strain, lack of material and other undesirable phenomena.

MANUFACTURE DWG		 东莞市讯普电子科技有限公司 DongGuan XunPu Electronics Co.,Ltd	
UNLESS OTHERWISE SPECIFIED TOLERANCES			
DECIMALS:	ANGLES:	TITLE: SH1.0MM HOUSING	
.X±0.30	X.*±1°	PAR	WAFER-SH1.0-NPJK
.XX±0.20		DWN	
.XXX±0.10		CHKD	
		APVD	
		SCALE:1:1	UNIT:MM
		CUSTOMER COPY	SIZE:A4
			SHEET:1F1
			REV:A