

Part Number : 349590340

Product Description : Mini50 Unsealed Receptacle, 3 Rows, with CPA, 34 Circuits,

Polarization Option A, Black

Status: Active

Series Number: 34959

Product Category: Connector Housings

Documents & Resources

Drawings

Drawing 349590340_sd.pdf
Packaging Design Drawing PK-31301-538-001.pdf
Packaging Design Drawing PK-31301-538-001.pdf

3D Models and Design Files

3D Model 349590340_stp.zip

Specifications

Application Specification 349590001-AS-CH-000.pdf
Application Specification AS-34959-001-001.pdf
Product Specification PS-34959-001-001.pdf
Test Summary TS-34961-001-001.pdf

Product Environment Compliance

Compliance

| GADSL/IMDS | Compliant |
|--------------------|--|
| China RoHS | © |
| EU ELV | Compliant per 2000/53/EC |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21 |
| REACH SVHC | Not Contained per D(2024)4144-DC (27 June 2024) |
| EU RoHS | Compliant per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C

- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| Status | Active |
|----------------|---|
| Category | Connector Housings |
| Series | 34959 |
| Description | Mini50 Unsealed Receptacle, 3 Rows, with CPA, 34 Circuits, Polarization Option A, Black |
| Application | Automotive, Power, Wire-to-Board |
| Product Family | Mini50 Connection Systems |
| Product Name | Mini50 |
| UPC | 887191704418 |

Physical

| Circuits (maximum) | 34 |
|-------------------------------|------------|
| Color - Resin | Black |
| Gender | Receptacle |
| Glow-Wire Capable | No |
| Keying to Mating Part | Yes |
| Lock to Mating Part | Yes |
| Material - Resin | Nylon |
| Net Weight | 5.700/g |
| Number of Rows | 3 |
| Packaging Type | Bag |
| Panel Mount | No |
| Pitch - Mating Interface | 2.00mm |
| Pitch - Termination Interface | 2.00mm |
| Polarization | А |
| Polarized to Mating Part | Yes |
| Stackable | No |

| Temperature Range - Operating | -40° to +105°C |
|-------------------------------|----------------|
| | |

Mates With / Use With

Mates with Part(s)

| Description | Part Number |
|---|------------------|
| Mini50 Unsealed Vertical Hybrid Header, 3 Rows, 34 Circuits, Polarization Option A, Black, Tray | <u>349580340</u> |
| Mini50 Unsealed Vertical Hybrid Header, 3 Rows, 34 Circuits, Polarization Option A, Black, Tube | <u>349587340</u> |
| Mini50 Unsealed Vertical Hybrid Header, 3 Rows, 34 Circuits, Polarization Option A, Black, Tape and Reel | <u>349588340</u> |
| Mini50 Unsealed Right-Angle Hybrid Header, UL 94 HB, 34 Circuits, Polarization A, Black, Tube | <u>349617343</u> |
| Mini50 Unsealed Right-Angle Hybrid Header, UL 94 HB, 34 Circuits, Polarization A, Black, Tape and Reel | <u>349618343</u> |
| Mini50 Unsealed Right-Angle Hybrid Header, UL 94 HB, 34 Circuits, Polarization A, Black, Tray | <u>349610343</u> |
| Mini50 Unsealed Right-Angle Headers | <u>213355</u> |

Use with Part(s)

| Description | Part Number |
|--|-------------|
| CTX50 Unsealed Receptacle Terminals | 560023 |

This document was generated on Sep 15, 2024