







APPROVED: _____
DATE: _____ TITLE: _____

Rev	AWO #	Description	Date	Appr
-		RELEASED	11/18/21	
A		UPDATE SPEC.	5/27/22	WX/MC
B		UPDATE SPEC.	4/18/24	WX/LL1



RECOMMENDED
PANEL CUT-OUT



SW-R2-1A-F-LXXX-2

	Lighted Actuator
W	Lighted White
R	Lighted Red
G	Lighted Green
Y	Lighted Yellow (Amber)
B	Lighted Blue

	Actuator Markings
1	
2	
3	
4	
5	

	LED Voltage
1	3V
2	6V
3	12V
4	24V
5	48V
6	110V
7	220V

SPECIFICATIONS:
Material:
Body: Nylon 66, Color Black, Rated UL 94V-0
Terminal: Brass, Silver plated
LED Terminal: Bare copper
Button: Nylon 66, Lighted color (See Chart). White color markings
Electrical:
The rated load: 250V AC, 6A
125V AC, 10A
DC rating specifications 20A, 12V DC
Contact resistance: 50 mohms max
Insulation resistance: 100 Mohms min
Dielectric withstanding voltage: 1500 VAC/5S min
Mechanical:
Electrical life: 10000 Cycles min
Temperature Rating:
Operating temperature: -25°C to +85°C
Environmental:
Lead free, RoHS compliant



Replace "x" in P/N with the corresponding switch color and marking

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS
ARE INCHES [MM]. TOLERANCES: EXCEPT AS NOTED

INCHES	HOLES
.X ±.10	ØX ±.10
.XX ±.020	ØXX ±.015
.XXX ±.015	ØXXX ±.010

DRAWN	JJ	11/18/21
CHECKED	RC	11/18/21
APPROVED		

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY
AND SHOULD NOT BE USED WITHOUT PRIOR WRITTEN
PERMISSION FROM ADAM TECH

ADAM
TECH

909 Rahway Avenue,
Union, NJ 07083
Phone: 908-687-5000
Fax: 908-687-5710

TITLE
SWITCH, MINIATURE ROCKER, SPST,
ON-OFF, .187 [4.75MM], LIGHTED

SIZE X	PART NO. SW-R2-1A-F-LXXX-2	REV. B
REF: S00206C	SCALE: NTS	SHEET 1 OF 1