

BUSHING FINISH	SILVER					
LEAD FINISH	TIN/SILVER					
CAPACITANCE	1000pF +100/-0%					
TEMP, RANGE	-55°C/+125°C					
CURRENT	25 AMPS					
WORKING VOLTAGE	125°C 500 VDC					
DC RESISTANCE	.01 🗆 hms MAX.					
IL=PER MIL-STD-220						
FREQ. MHz	I.L. (db)					
100MHz	15					
300MHz	25					
1 GHz	35					
10 GHz	40					
SCHEMATIC 0O						



PART: SF102P

BAG:

SCI 54F-806-007

DATE CODE LOT NO. QTY/BAG

NOTES:

RoHS

COMPLIANT

1. HARDWARE IS INCLUDED.

2. PRE-FLATTEN/NOTCH DIMENSIONS ARE:

TOP: .386±.010 BOTTOM: .448±.010

		5	REV.	TOLERANCES UNLESS OTHERWISE SPECIFIED		FAIRVIEW
		טט	_ ∷	Fractions ± 1/64 Dec××±	SPECTRUM CONTROL I	PENNSYLVANIA nc.
	2		Decxxx± .010	Dwn.P. WELLS	Description	
	2	병	Angles ±0° 30′	Date 5-30-06	FLTR., SING., FT, BSHG.	
		, C	1 7	CODE IDENT. NO.	Engr. STRUCHEN	E4E 000 007
		3	5 古	OLSP2	Scale NONE	54F-806-007

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

API Technologies: 54F-806-007