

Part Number: 16020088

Product Description: SL Crimp Terminal, Series 70058, Female, 24-22 AWG, with 0.76μm Selective Gold (Au) Plated Contact,

Reel

Series Number: 70058

Status: Active

Product Category: Crimp Terminals Engineering Number: 70058-0026 Packaging Alternative: 16020104 (Bag)



Documents & Resources

Drawings

Drawing 016020088_sd.pdf

Specifications

Product Specification PS-70058-001.pdf Product Specification PS-70400-001.pdf Test Summary TS-70058-001-001.pdf

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	©
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	Active
Category	Crimp Terminals
Series	70058
Description	SL Crimp Terminal, Series 70058, Female, 24-22 AWG, with 0.76µm Selective Gold (Au) Plated Contact, Reel
Application	Signal, Wire-to-Board, Wire-to-Wire
Product Family	SL Modular Connectors
Product Name	CyClone,SL
UPC	800753596030

Physical

Gender	Female
Material - Metal	Phosphor Bronze
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Net Weight	0.073/g
Packaging Type	Reel
Plating min - Mating	0.750μm
Plating min - Termination	2.000µm
Termination Interface Style	Crimp or Compression
Wire Insulation Diameter	1.63mm max.
Wire Size (AWG)	22, 24
Wire Size mm²	N/A

Solder Process Data

Lead-Free Process Capability	N/A
Lead Free Freeds capability	13773

Use with Part(s)

Description	Part Number
SL Single Row Crimp Housings and CPA Retainers	<u>70066</u>
SL Dual Row Crimp Housings	70450

Application Tooling

Global

Description	Part Number
Insertion Tool for 70021,70028, 70110, 71851 Terminals / Extraction Tool for 91821 Terminals	<u>11020022</u>
PremiumGrade Hand Crimp Tool for SL Crimp Terminals, 24-22 AWG and 36-32 AWG	<u>638118700</u>
FineAdjust Applicator for SL Crimp Terminals, for 24-22 AWG Wire with Insulation Diameter 1.40-1.63mm	639023200
T2 Terminator for Female Crimp Terminal	639123200

This document was generated on Sep 19, 2024