



**Product:** [5100FE](#)

Security & Sound, 2 Conductor 14 AWG, BC, Shielded, CL3R, FPLR

Product Description

Security & Commercial Audio Cable, Riser-CL3R-FPLR, 2-14 AWG stranded bare copper conductors with polypropylene insulation, Beldfoil® shield and PVC jacket with ripcord

Technical Specifications

Product Overview

|                        |                                                              |
|------------------------|--------------------------------------------------------------|
| Suitable Applications: | Intercom/PA Systems, Sound/Audio Systems, Fire Alarm Systems |
|------------------------|--------------------------------------------------------------|

Construction Details

Conductor

| Element      | No. of Elements | Size   | Stranding | Material         |
|--------------|-----------------|--------|-----------|------------------|
| Conductor(s) | 2               | 14 AWG | 19x26     | BC - Bare Copper |

Insulation

| Element      | Material           | Nom. Thickness     | Nom. Insulation Diameter | Color Code   |
|--------------|--------------------|--------------------|--------------------------|--------------|
| Conductor(s) | PP - Polypropylene | 0.011 in (0.28 mm) | 0.092 in (2.3 mm)        | Black, White |

Outer Shield

| Shield Type | Material                | Coverage | Drainwire Type   |
|-------------|-------------------------|----------|------------------|
| Tape        | Bi-Laminate (Alum+Poly) | 100%     | 22 AWG (7x30) TC |

Outer Jacket

| Material                 | Nom. Thickness     | Nom. Diameter      | Ripcord |
|--------------------------|--------------------|--------------------|---------|
| PVC - Polyvinyl Chloride | 0.017 in (0.43 mm) | 0.222 in (5.64 mm) | Yes     |

|                                   |                    |
|-----------------------------------|--------------------|
| Overall Cable Diameter (Nominal): | 0.222 in (5.64 mm) |
|-----------------------------------|--------------------|

Electrical Characteristics

Electricals

| Element      | Nom. Conductor DCR | Nom. Capacitance Cond-to-Cond | Nom. Capacitance Cond-to-Other (Conds + Shield) | Max. Current                 |
|--------------|--------------------|-------------------------------|-------------------------------------------------|------------------------------|
| Conductor(s) | 2.54 Ohm/1000ft    | 54 pF/ft (180 pF/m)           | 97.25 pF/ft (319.1 pF/m)                        | 25 Amps per conductor @ 30°C |

Voltage

| UL Voltage Rating  |
|--------------------|
| 300 V (CL3R, FPLR) |

Mechanical Characteristics

Temperature

| UL Temperature | Operating      |
|----------------|----------------|
| 75°C           | -20°C to +75°C |

Bend Radius

| Stationary Min. | Installation Min. |
|-----------------|-------------------|
| 2.2 in (56 mm)  | 2.2 in (56 mm)    |

|                    |                      |
|--------------------|----------------------|
| Max. Pull Tension: | 104.1 lbs (47.22 kg) |
| Bulk Cable Weight: | 37 lbs/1000ft        |

Standards and Compliance

|                                  |                                                                                                                           |
|----------------------------------|---------------------------------------------------------------------------------------------------------------------------|
| Environmental Suitability:       | Indoor - Riser, Indoor                                                                                                    |
| Flammability / Reaction to Fire: | UL 1666 Riser, IEEE 1202 FT4, IEC 60332-1-2                                                                               |
| CPR Compliance:                  | CPR Euroclass: Eca                                                                                                        |
| NEC / UL Compliance:             | Article 725, Article 760, CL3R, FPLR                                                                                      |
| European Directive Compliance:   | EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE) |
| UK Regulation Compliance:        | UKCA Mark                                                                                                                 |
| APAC Compliance:                 | China RoHS II (GB/T 26572-2011)                                                                                           |
| Plenum Number:                   | 6100FH                                                                                                                    |

History

|                      |                                                  |
|----------------------|--------------------------------------------------|
| Update and Revision: | Revision Number: 0.529 Revision Date: 02-15-2024 |
|----------------------|--------------------------------------------------|

Part Numbers

Variants

| Item #          | Color  | Putup Type   | Length   | UPC/EAN       | Footnote |
|-----------------|--------|--------------|----------|---------------|----------|
| 5100FE.00152    | Chrome | Reel         | 152 m    | 8719605007704 |          |
| 5100FE.00305    | Chrome | Reel         | 305 m    | 8719605007728 |          |
| 5100FE.001000   | Chrome | Reel         | 1,000 m  | 8719605007698 |          |
| 5100FE 008500   | Gray   | Reel         | 500 ft   | 612825156222  |          |
| 5100FE 0081000  | Gray   | Reel         | 1,000 ft | 612825156246  | C        |
| 5100FE 008U1000 | Gray   | UnReel       | 1,000 ft | 612825423591  |          |
| 5100FE 008Z1000 | Gray   | ReelTuff Box | 1,000 ft | 612825156260  |          |
| 5100FE.003000   | Gray   | Reel         | 3,000 m  | 8719605007711 |          |
| 5100FE 0021000  | Red    | Reel         | 1,000 ft | 612825423584  | C        |
| 5100FE 002Z1000 | Red    | ReelTuff Box | 1,000 ft | 612825156239  |          |

© 2024 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.