

## PCB terminal block - MKDSN 1,5/ 8 BD:NZ 4338 - 1987041

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

PCB terminal block, nominal current: 13.5 A, pitch: 5 mm, number of positions: 8, connection method: Screw connection with tension sleeve, mounting: Wave soldering, conductor/PCB connection direction: 0 °, color: green



### Key Commercial Data

|              |                                                                                                       |
|--------------|-------------------------------------------------------------------------------------------------------|
| Packing unit | 50 pc                                                                                                 |
| GTIN         | <br>4 017918 924621 |
| GTIN         | 4017918924621                                                                                         |

### Technical data

#### Item properties

|                       |                |
|-----------------------|----------------|
| Number of positions   | 8              |
| Drive form screw head | Slotted (L)    |
| Screw thread          | M3             |
| Pin layout            | Linear pinning |

#### Dimensions for the product

|                             |         |
|-----------------------------|---------|
| Length [ l ]                | 8.1 mm  |
| Width [ w ]                 | 40 mm   |
| Height [ h ]                | 13.5 mm |
| Pitch                       | 5 mm    |
| Height (without solder pin) | 10 mm   |
| Solder pin [P]              | 3.5 mm  |
| Pin spacing                 | 5 mm    |
| Dimension a                 | 35 mm   |

#### Dimensions for PCB design

|               |        |
|---------------|--------|
| Hole diameter | 1.3 mm |
| Pin spacing   | 5 mm   |

#### Packaging information

|                            |                     |
|----------------------------|---------------------|
| Type of packaging          | packed in cardboard |
| Pieces per package         | 50                  |
| Denomination packing units | Pcs.                |

# PCB terminal block - MKDSN 1,5/ 8 BD:NZ 4338 - 1987041

## Technical data

### Air clearances and creepage distances

|         |       |
|---------|-------|
| Voltage | 250 V |
|---------|-------|

### Standards and Regulations

|                                  |        |
|----------------------------------|--------|
| Connection in acc. with standard | EN-VDE |
|                                  | CSA    |

### Environmental Product Compliance

|            |                                                                                                     |
|------------|-----------------------------------------------------------------------------------------------------|
| REACH SVHC | Lead 7439-92-1                                                                                      |
| China RoHS | Environmentally Friendly Use Period = 50                                                            |
|            | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

## Approvals

### Approvals

#### Approvals

DNV GL / CSA / IECEx CB Scheme / SEV / EAC / cULus Recognized

#### Ex Approvals

### Approval details

|        |                                                                           |            |
|--------|---------------------------------------------------------------------------|------------|
| DNV GL | <a href="http://exchange.dnv.com/tari/">http://exchange.dnv.com/tari/</a> | TAE00001EV |
|--------|---------------------------------------------------------------------------|------------|

|                    |                                                                                     |                                                                                                                                         |       |
|--------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|-------|
| CSA                |  | <a href="http://www.csagroup.org/services-industries/product-listing/">http://www.csagroup.org/services-industries/product-listing/</a> | 13631 |
|                    | D                                                                                   | B                                                                                                                                       |       |
| Nominal voltage UN | 300 V                                                                               | 150 V                                                                                                                                   |       |
| Nominal current IN | 10 A                                                                                | 10 A                                                                                                                                    |       |
| mm²/AWG/kcmil      | 28-14                                                                               | 28-14                                                                                                                                   |       |

|                    |                                                                                     |                                                           |         |
|--------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------|---------|
| IECEE CB Scheme    |  | <a href="http://www.iecee.org/">http://www.iecee.org/</a> | CH-8225 |
|                    |                                                                                     |                                                           |         |
| Nominal voltage UN | 250 V                                                                               |                                                           |         |
| Nominal current IN | 13.5 A                                                                              |                                                           |         |
| mm²/AWG/kcmil      | 1.5                                                                                 |                                                           |         |

## PCB terminal block - MKDSN 1,5/ 8 BD:NZ 4338 - 1987041

### Approvals

|                    |                                                                                   |                                                                                                                                                     |            |
|--------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| SEV                |  | <a href="https://www.electrosuisse.ch/de/meta/shop/produktezertifikate.html">https://www.electrosuisse.ch/de/meta/shop/produktezertifikate.html</a> | IK-3542-M1 |
| Nominal voltage UN |                                                                                   | 250 V                                                                                                                                               |            |
| Nominal current IN |                                                                                   | 13.5 A                                                                                                                                              |            |
| mm²/AWG/kcmil      |                                                                                   | 1.5                                                                                                                                                 |            |

|     |                                                                                   |         |
|-----|-----------------------------------------------------------------------------------|---------|
| EAC |  | B.01742 |
|-----|-----------------------------------------------------------------------------------|---------|

|                    |                                                                                   |                                                                                                                                                       |                 |
|--------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| cULus Recognized   |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | E60425-19770427 |
|                    | D                                                                                 | B                                                                                                                                                     |                 |
| Nominal voltage UN | 300 V                                                                             | 300 V                                                                                                                                                 |                 |
| Nominal current IN | 10 A                                                                              | 10 A                                                                                                                                                  |                 |
| mm²/AWG/kcmil      | 30-14                                                                             | 30-14                                                                                                                                                 |                 |

Phoenix Contact 2018 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact:

1987041