

1078592

https://www.phoenixcontact.com/us/products/1078592

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sleeve housing COM, for single locking latch, material: Die-cast aluminum, salt water resistant, cable outlets: 1, lateral, 1x M25, height: 68 mm, cable gland: none, Standard

Your advantages

• Good shielding in the event of electromagnetic interference

Commercial data

| Item number | 1078592 |
|--------------------------------------|---------------------|
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | BF59 |
| Product key | BF7APP |
| Catalog page | Page 653 (C-2-2019) |
| GTIN | 4055626794105 |
| Weight per piece (including packing) | 81.8 g |
| Weight per piece (excluding packing) | 81 g |
| Customs tariff number | 76169990 |
| Country of origin | CN |



1078592

https://www.phoenixcontact.com/us/products/1078592

Technical data

Product properties

| Product type | Housing with locking latch |
|------------------------------|----------------------------|
| Housing type | Sleeve housing |
| Product family | HC-COM |
| Application | Standard |
| Туре | COM |
| No. of cable outlets | 1 |
| Type of the screw connection | 1x M25 |
| Туре | Tall design |
| Cable outlet | lateral |
| Pg screw connection | none |
| Data management status | |
| Article revision | 01 |

Dimensions

| Dimensional drawing | 48,8 |
|---------------------|---------|
| Width | 39 mm |
| Height | 68 mm |
| Length | 48.8 mm |

Material specifications

| Housing material | Die-cast aluminum, salt water resistant |
|------------------|---|
|------------------|---|

Mechanical properties

Mechanical data

| Type of the screw connection | 1x M25 |
|------------------------------|--------|
| Locking type | Pin |

Mounting

| Thread type | () |
|-------------|----|

Environmental and real-life conditions

Ambient conditions

| Degree of protection | IP66 |
|---------------------------------|---------------|
| Impact strength | IK06 |
| Ambient temperature (operation) | -40 °C 125 °C |





https://www.phoenixcontact.com/us/products/1078592



Drawings

Dimensional drawing







1078592

https://www.phoenixcontact.com/us/products/1078592

Approvals

🌣 To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/1078592



cUL RecognizedApproval ID: E255026



UL RecognizedApproval ID: E255026



EAC

Approval ID: RU C-DE.BL08.B.00511

cULus Recognized



1078592

https://www.phoenixcontact.com/us/products/1078592

Classifications

UNSPSC 21.0

ECLASS

| 27440202 |
|----------|
| 27440202 |
| 27440202 |
| |
| EC000437 |
| |
| |

31261500



1078592

https://www.phoenixcontact.com/us/products/1078592

Environmental product compliance

REACH candidate substance (CAS No.)

| EU RoHS | |
|---|--|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
| China RoHS | |
| Environment friendly use period (EFUP) | EFUP-E |
| | No hazardous substances above the limits |
| EU REACH SVHC | |

No substance above 0.1 wt%



1078592

https://www.phoenixcontact.com/us/products/1078592

Accessories

HC-COM-HCWS-PLR-BK - Protective cover

1079394

https://www.phoenixcontact.com/us/products/1079394



Protective cover COM, with single locking latch, protective cover material: PA, height: 20.5 mm, seal: yes, Standard, for socket inserts

HC-COM-HCWS-PL-BK - Protective cover

1079395

https://www.phoenixcontact.com/us/products/1079395



Protective cover COM, with single locking latch, protective cover material: PA, height: 20.5 mm, seal: no, Standard, for pin inserts



1078592

https://www.phoenixcontact.com/us/products/1078592

G-INS-M25-M68N-NNES-S - Cable gland

1411165

https://www.phoenixcontact.com/us/products/1411165



Cable gland, material for screw connection: Brass, nickel-plated, application: Standard, external cable diameter 11 mm ... 17 mm, shielding: no, connecting thread: M25 x 1.5, color: silver, with O-ring

G-INSEC-M25-S68N-NCRS-S - Cable gland

1411190

https://www.phoenixcontact.com/us/products/1411190



Cable gland, material for screw connection: Brass, nickel-plated, application: EMC, external cable diameter 11 mm \dots 16 mm, shielding: yes, connecting thread: M25 x 1.5, color: silver, with O-ring



1078592

https://www.phoenixcontact.com/us/products/1078592

US-EMLP-HA (20X9) - Plastic label

0830989

https://www.phoenixcontact.com/us/products/0830989



Plastic label, Card, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: adhesive, lettering field size: 20 x 9 mm, Number of individual labels: 70

US-EMLP-HA (20X9) CUS - Plastic label

0830995

https://www.phoenixcontact.com/us/products/0830995

Plastic label, Card, can be ordered: by card, white, labeled, can be labeled with: THERMOMARK CARD, mounting type: adhesive, lettering field size: 20 x 9 mm, Number of individual labels: 70





1078592

https://www.phoenixcontact.com/us/products/1078592

WP-G HF IP66 M25 BK - Screw connection

3240899

https://www.phoenixcontact.com/us/products/3240899



Cable gland, metric thread, IP66 protection, straight

WP-G HF IP69K M25 BK - Screw connection

3240885

https://www.phoenixcontact.com/us/products/3240885



Cable gland, metric thread, IP68/69k protection, straight



1078592

https://www.phoenixcontact.com/us/products/1078592

WP-GA HF IP66 M25 BK - Screw connection

3240927

https://www.phoenixcontact.com/us/products/3240927

Cable gland, metric thread, IP66 protection, angled



WP-GA HF IP69K M25 BK - Screw connection

3240913

https://www.phoenixcontact.com/us/products/3240913

Cable gland, metric thread, IP68/69k protection, angled





1078592

https://www.phoenixcontact.com/us/products/1078592

WP-GR HF IP66 M25 BK - Screw connection

3240955

https://www.phoenixcontact.com/us/products/3240955



Cable gland, metric thread, IP66 protection, with strain relief

WP-GR HF IP69K M25 BK - Screw connection

3240941

https://www.phoenixcontact.com/us/products/3240941



Cable gland, metric thread, IP68/69k protection, with strain relief



1078592

https://www.phoenixcontact.com/us/products/1078592

WP-G PP HF M25 - Screw connection

3240999

https://www.phoenixcontact.com/us/products/3240999



Cable gland made from PP with metric thread, IP65 protection

WP-GT PP HF M25 - Screw connection

3241013

https://www.phoenixcontact.com/us/products/3241013



Cable gland made from PP with metric thread, rotatable, IP54 protection



1078592

https://www.phoenixcontact.com/us/products/1078592

WP-G BRASS IP40 M25 - Screw connection

3241048

https://www.phoenixcontact.com/us/products/3241048



Cable gland made from brass with metric thread, IP40 protection

WP-GT BRASS M25 - Screw connection

3241034

https://www.phoenixcontact.com/us/products/3241034



Cable gland made from brass with metric thread, rotatable, IP40 protection



1078592

https://www.phoenixcontact.com/us/products/1078592

WP-G BRASS IP65 M25 - Screw connection

3241062

https://www.phoenixcontact.com/us/products/3241062



Cable gland made from brass with metric thread, IP65 protection

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com