






Heyco® -Tite Aluminum Liquid Tight Cordgrips Straight-Thru, NPT Hubs

The Ultimate in Liquid Tight Strain Relief Protection

- Aluminum construction provides excellent durability and performance for most industrial applications.
- For use in both indoor and outdoor applications to prevent cable pull-out, control arc of bend, and to provide a tight seal against environmental elements such as dirt, moisture, and coolants.
- IP 67 rated.
- Approved for NEMA 6 applications.
- Protect cable from damage and pull-out and are used in conduit hubs or knock-outs at the point where the electrical cable is to be terminated.
- Unique design with a combination tightening surface that includes both a hex area and a knurled surface.
- Anti-friction washer allows for easier compression.

CABLE DIA. RANGE				PART NO.	THREAD SIZE		PART DIMENSIONS								
Minimum		Maximum					Machined Aluminum	A Clearance Hole Dia.		B Max. O.A. Length		C Thread Length		D Wrenching Flat Size	
in.	mm.	in.	mm.					in.	mm.	in.	mm.	in.	mm.	in.	mm.
.875	22,2	1.000	25,4	M5058	NPT 1		1.38	35,1	2.5	63,5	.69	17,5	2.25	57,2	
1.000	25,4	1.125	28,6	M5059											
1.125	28,6	1.120	31,8	M5060											
1.250	31,8	1.375	34,9	M5061											
.562	14,3	.688	17,5	M5062	NPT 1-1/4		1.72	43,7	2.50	63,5	.69	17,5	2.25	57,2	
.688	17,5	.812	20,6	M5063											
.750	19,1	.875	22,2	M5064											
.875	22,2	1.000	25,4	M5065											
1.000	25,4	1.125	28,6	M5066											
1.125	28,6	1.250	31,8	M5067											
1.250	31,8	1.375	34,9	M5068											
.562	14,3	.688	17,5	M5069*											
.688	17,5	.812	20,6	M5070	NPT 1-1/2		1.97	50,0	2.50	63,5	.69	17,5	2.25	57,2	
.750	19,1	.875	22,2	M5071											
.875	22,2	1.000	25,4	M5072											
1.000	25,4	1.125	28,6	M5073											
1.125	28,6	1.250	31,8	M5074											
1.250	31,8	1.375	34,9	M5075											
1.250	31,8	1.375	34,9	M5080											
1.312	33,3	1.437	36,5	M5081											
1.438	36,5	1.562	39,7	M5082	NPT 2		2.46	62,5	3.12	79,2	.80	20,3	2.83	71,9	
1.562	39,7	1.688	42,9	M5083											
1.688	42,9	1.812	46,0	M5084											

Assembled O-ring **INCLUDED**. *Not UL Listed or CSA Certified.
Locknut not included - See page 9 for Metal Locknuts.



SUGGESTED CLEARANCE HOLE
FOR NON-THREADED MOUNTING

Quick
Specs

Material
Certifications

- Aluminum with Neoprene Sealing Gland and Viton® O-Ring
- UL Listed under Underwriters' Laboratories File E51579
- CSA Certified by Canadian Standard Association File 93876C
- Approved for NEMA 6 Applications

Flammability Rating
Temperature Rating
IP Rating

94V-2
-40°F (-40°C) to 250°F (121°C)
IP 67