

Actuator

46-
2W28.3CP0.001

Distribution by
DigiKey

DigiKey



<https://digikey.eao.com/p/46-2W28.3CP0.001>

Your product:



46-2W28.3CP0.001 Actuator

Loading . .

FRONT

Front form:	round
Front dimension:	Ø 30 mm
Front bezel colour:	Silver
Front bezel material:	Metal

MOUNTING

Design:	raised
Mounting cut-out:	Ø 22.3 mm

OPERATING-/INDICATION PART

Lever material:	plastic
Lever shape:	short
Lever bar colour:	White
Lever colour:	Red

ELECTRICAL CHARACTERISTICS

Protection class:	II
-------------------	----

MECHANICAL CHARACTERISTIC

Mechanical lifetime:	1 Mio. cycles of operation
Switching positions:	2 positions
Switching action:	Maintained - Maintained

Weight: 0.038 kg

Tightening torque: 2 ... 3 Nm (17.7 ... 26.6 Lb-in)

Switching angle: 90°

AMBIENT CONDITION

Vibration resistance: 5g f= 2...500Hz (EN-IEC 60068-2-6)

Climate resistance: +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)

Operating temperature: – 25 °C ... + 55 °C

Shock resistance: 30g, 18ms (EN-IEC 60068-2-27)
50g, 11ms (EN-IEC 60068-2-27)

IK front protection: IK03

IP front protection: IP65

CERTIFICATE

Standards: CSA C22-2, IEC EN 60947-1, IEC EN 60947-5-1, UL508

Conformities: CE

OTHER


Short Description: Actuator, Ø 22.3 mm, Ø 30 mm, illuminative, Red, short, round, Silver, Metal, Maintained - Maintained, IP65, IK03

Housing material: Plastic

Housing colour: Black

max. number of switching elements: 2

Dimension drawings:



Switching positions:

