


## Surface-Mounting DPDT Relay

- ROHS compliant.
- Long terminals ideal for soldering and mounting reliability.
- Space-saving inside-L terminal.
- High dielectric strength between coil and contacts (2,000 VAC), and between contacts of different polarity (1,500 VAC).
- High impulse withstand voltages between coil and contacts, and between contacts of different polarity (2,500 V, 2 10 µs: Bellcore requirements).
- Low power consumption (140 mW).
- Bifurcated crossbar contact (Au-clad) and Fully sealed construction for high reliability.
- Applicable to IRS.
- High sealability after IRS.



- Ultra-miniature at 15 x 7.5 x 9.4 mm (L x W x H).
- Through-hole terminal is available
- EN60950 Supplementary Insulation-certified type is available.

## Ordering Information

Classification			Single-side Stable	Single-winding latching	Double-winding latching	Single-side stable EN60950/EN41003	
DPDT	Fully sealed	Through-hole terminal	G6S-2	G6SU-2	G6SK-2	G6S-2-Y	
		Surface mounting terminal	Inside-L	G6S-2G	G6SU-2G	G6SK-2G	G6S-2G-Y
			Outside-L	G6S-2F	G6SU-2F	G6SK-2F	G6S-2F-Y

**Note:** 1. When ordering, add the rated coil voltage to the model number.  
Example: G6S-2F 12 VDC

2. When ordering tape packing, add -TR" to the model number.  
Example: G6S-2F-TR 12 VDC

Be sure since -TR" is not part of the relay model number, it is not marked on the relay case.

### Model Number Legend

G6S           VDC

1    2    3    4    5

#### 1. Relay Function

- None: Single-side stable
- U: Single-winding latching
- K: Double-winding latching

#### 2. Contact Form

- 2: DPDT

#### 3. Terminal Shape

- None: Through-hole terminal
- G: Inside-L surface mounting terminal
- F: Outside-L surface mounting terminal

#### 4. Approved Standards

- None: UL/CSA
- Y: EN60950

#### 5. Rated Coil Voltage

- 4.5, 5, 12, 24 VDC

## Specifications

### ■ Coil Ratings

#### Single-side Stable Type (G6S-2, G6S-2F, G6S-2G)

<b>Rated voltage</b>	4.5 VDC	5 VDC	12 VDC	24 VDC
<b>Rated current</b>	31.0 mA	28.1 mA	11.7 mA	8.3 mA
<b>Coil resistance</b>	145 Ω	178 Ω	1,028 Ω	2,880 Ω
<b>Must operate voltage</b>	75% max. of rated voltage			
<b>Must release voltage</b>	10% min. of rated voltage			
<b>Max. voltage</b>	200% of rated voltage at 23°C		170% of rated voltage at 23°C	
<b>Power consumption</b>	Approx. 140 mW		Approx. 200 mW	

#### Single-winding Latching Type (G6SU-2, G6SU-2F, G6SU-2G)

<b>Rated voltage</b>	4.5 VDC	5 VDC	12 VDC	24 VDC
<b>Rated current</b>	22.2 mA	20 mA	8.3 mA	6.3 mA
<b>Coil resistance</b>	203 Ω	250 Ω	1,440 Ω	3,840 Ω
<b>Coil inductance (H) (ref. value)</b>	<b>Armature OFF</b>	0.27	0.36	5.80
	<b>Armature ON</b>	0.14	0.18	3.79
<b>Must set voltage</b>	75% max. of rated voltage			
<b>Must reset voltage</b>	75% min. of rated voltage			
<b>Max. voltage</b>	180% of rated voltage at 23°C			
<b>Power consumption</b>	Approx. 100 mW		Approx. 150 mW	

#### Double-winding Latching Type (G6SK-2, G6SK-2F, G6SK-2G)

<b>Rated voltage</b>	4.5 VDC	5 VDC	12 VDC	24 VDC		
<b>Rated current</b>	44.4 mA	40 mA	16.7 mA	12.5 mA		
<b>Coil resistance</b>	101 Ω	125 Ω	720 Ω	1,920 Ω		
<b>Coil inductance (H) (ref. value)</b>	<b>Set</b>	<b>Armature OFF</b>	0.12	0.14	0.60	1.98
		<b>Armature ON</b>	0.074	0.088	0.41	1.23
	<b>Reset</b>	<b>Armature OFF</b>	0.082	0.098	0.46	1.34
		<b>Armature ON</b>	0.14	0.16	0.54	2.23
<b>Must set voltage</b>	75% max. of rated voltage					
<b>Must reset voltage</b>	75% min. of rated voltage					
<b>Max. voltage</b>	170% of rated voltage at 23°C		140% of rated voltage at 23°C			
<b>Power consumption</b>	Approx. 200 mW		Approx. 300 mW			

- Note:**
1. The rated current and coil resistance are measured at a coil temperature of 23°C with a tolerance of ±10%.
  2. Operating characteristics are measured at a coil temperature of 23°C.
  3. The maximum voltage is the highest voltage that can be imposed on the relay coil.

## Surface-Mounting Signal Relay – G6S

Single-side Stable EN60950 Approved Type (G6S-2-Y, G6S-2F-Y, G6S-2G-Y)

Rated voltage	5 VDC	12 VDC	24 VDC
Rated current	40 mA	16.7 mA	9.6 mA
Coil resistance	125 $\Omega$	720 $\Omega$	2,504 $\Omega$
Must operate voltage	75% max. of rated voltage		
Must release voltage	10% min. of rated voltage		
Max. voltage	170% of rated voltage at 23°C		170% of rated voltage at 23°C
Power consumption	Approx. 200 mW		Approx. 230 mW

**Note:** 1. The rated current and coil resistance are measured at a coil temperature of 23°C with a tolerance of  $\pm 10\%$ .

2. Operating characteristics are measured at a coil temperature of 23°C.

3. The maximum voltage is the highest voltage that can be imposed on the relay coil.

### ■ Contact Ratings

Load	Resistive load ( $\cos\phi = 1$ )
Rated Load	0.5 A at 125 VAC; 2 A at 30 VDC
Contact material	Ag (Au-alloy)
Rated Carry Current	2 A
Max. switching voltage	250 VAC, 220 VDC
Max. switching current	2 A
Max. switching power	62.5 VA, 60 W
Failure rate (reference value) (see note)	10 $\mu$ A at 10 mVDC

**Note:** P level:  $\lambda_{60} = 0.1 \times 10^{-6}$ /operation. This value was measured at a switching frequency of 120 operations/min and the criterion of contact resistance is 50 $\Omega$ . This value may vary depending on the operating environment. Always double-check relay suitability under actual operating conditions.

# Surface-Mounting Signal Relay – G6S

## ■ Characteristics

<b>Contact resistance (Note)</b>	75 mΩ max.
<b>Operate (set) time (Note 2)</b>	4 ms max. (mean value: approx. 2.5 ms; latching type: approx. 2 ms)
<b>Release (reset) time (Note 2)</b>	4 ms max. (mean value: approx. 1.5 ms; latching type: approx. 2 ms)
<b>Max. operating frequency</b>	Mechanical: 36,000 operations/hr Electrical: 1,800 operations/hr (under rated load)
<b>Insulation resistance (Note 3)</b>	1,000 MΩ min. (at 500 VDC)
<b>Dielectric strength</b>	2,000 VAC, 50/60 Hz for 1 min between coil and contacts 1,000 VAC, 50/60 Hz for 1 min between coil and contacts (double-winding latching) 1,500 VAC, 50/60 Hz for 1 min between contacts of different polarity 1,000 VAC, 50/60 Hz for 1 min between contacts of same polarity 500 VAC, 50/60 Hz for 1 min between set and reset coil (double-winding latching)
<b>Impulse withstand voltage</b>	2,500 V (2 x 10 μs) between coil and contacts 1,500 V (10 x 160 μs) between coil and contacts (double-winding latching) 2,500 V (2 x 10 μs) between contacts of different polarity 1,500 V (10 x 160 μs) between contacts of same polarity (conforms to FCC Part 68)
<b>Vibration resistance</b>	Destruction: 10 to 55 to 10 Hz, 2.5mm single amplitude (5mm double amplitude) Malfunction: 10 to 55 to 10 Hz, 1.65mm single amplitude (3.3mm double amplitude)
<b>Shock resistance</b>	Destruction: 1,000 m/s <sup>2</sup> (approx. 100G) Malfunction: 750 m/s <sup>2</sup> (approx. 175G)
<b>Endurance</b>	Mechanical: 100,000,000 operations min. (at 36,000 operations/hr) Electrical: 100,000 operations min. (2 A at 30 VDC, resistive load; 1,200 operations/hr) 100,000 operations min. (0.5 A at 125 VAC, resistive load)
<b>Ambient temperature</b>	Operating: -40°C to 85°C (with no icing), -40°C to 70°C (double-winding latching, 24 VDC)
<b>Ambient humidity</b>	Operating: 5% to 85%
<b>Weight</b>	Approx. 2 g

**Note:** The above values are initial values.

**Note: 1.** The contact resistance was measured with 10mA at 1 VDC with a voltage drop method.

**Note: 2.** Values in parentheses are actual values.

**Note: 3.** The insulation resistance was measured with a 500-VDC megohmmeter applied to the same parts as those used for checking the dielectric strength (except between the set and reset coil).

## ■ Approved Standards

### UL (File No. E41515)/CSA C22.2 (File No. LR24825)


Model	Contact form	Coil ratings	Contact ratings
G6S-2, G6S-2F, G6S-2G	DPDT	1.5 to 48 VDC	2 A, 30 VDC 0.3 A, 110 VDC 0.5 A, 125 VAC
G6SU2, G6SK-2, G6SU-2F G6SU2G, G6SK-2F, G6SK-2G		1.5 to 24 VDC	

### EN60950


Model	Contact form	Isolation category	Voltage
G6S-2-Y, G6S-2G-Y, G6S-2F-Y	DPDT	Supplementary Isolation	250 VAC

## Engineering Data


### Maximum Switching Power



### Ambient Temperature vs. Maximum Coil Voltage Single-side Stable




### Single-winding Latching Double-winding Latching




**Note:** The maximum coil voltage refers to the maximum value in a varying range of operating power voltage, not a continuous voltage.

### Reference Data

#### Ambient Temperature vs. Switching Current Single-side Stable




#### Single-winding Latching Double-winding Latching



## Recommended Soldering Method

Temperatures indicate the surface temperatures of the PCB.



- The thickness of cream solder to be applied should be within a range between 150 and 200 μm on OMRON's recommended PCB pattern.
- In order to perform correct soldering, it is recommended that the correct soldering conditions be maintained as shown below on the left side.

**Note:** The temperature profile indicates the temperature of the relay terminal section.



## Dimensions

Note: All units are in millimetres unless otherwise indicated.

### Single-side Stable


#### G6S-2, G6S-2-Y

Tolerance:  $\pm 0.3$




#### Footprint (Bottom View)

Tolerance:  $\pm 0.1$






#### Terminal Arrangement/ Internal Connections (Bottom View)




#### G6S-2F, G6S-2F-Y

Tolerance:  $\pm 0.3$




#### Footprint (Top View)

Tolerance:  $\pm 0.1$






#### Terminal Arrangement/ Internal Connections (Top View)




#### G6S-2G, G6S-2G-Y

Tolerance:  $\pm 0.3$




#### Footprint (Top View)

Tolerance:  $\pm 0.1$



#### Terminal Arrangement/ Internal Connections (Top View)





# Surface-Mounting Signal Relay – G6S

## Single-winding Latching


### G6SU-2

Tolerance:  $\pm 0.3$




### Footprint (Bottom View)

Tolerance:  $\pm 0.1$





### Terminal Arrangement/ Internal Connections (Bottom View)




### G6SU-2F

Tolerance:  $\pm 0.3$




### Footprint (Top View)

Tolerance:  $\pm 0.1$





### Terminal Arrangement/ Internal Connections (Top View)




### G6SU-2G

Tolerance:  $\pm 0.3$




### Footprint (Top View)

Tolerance:  $\pm 0.1$



### Terminal Arrangement/ Internal Connections (Top View)





# Surface-Mounting Signal Relay – G6S

## Double-winding Latching


### G6SK-2

Tolerance:  $\pm 0.3$




### Footprint (Bottom View)

Tolerance:  $\pm 0.1$





### Terminal Arrangement/ Internal Connections (Bottom View)




### G6SK-2F

Tolerance:  $\pm 0.3$




### Footprint (Top View)

Tolerance:  $\pm 0.1$





### Terminal Arrangement/ Internal Connections (Top View)




### G6SK-2G

Tolerance:  $\pm 0.3$




### Footprint (Top View)

Tolerance:  $\pm 0.1$




### Terminal Arrangement/ Internal Connections (Top View)






## ■ Tape Packing


When ordering, add “-TR” before the rated coil voltage for tape packing.  
 Tape type: TE2416R (Refer to EIAJ)  
 Reel type: R24E (Refer to EIAJ)  
 Relays per reel: 400



### G6S-2F, G6SU-2F, G6SK-2F, G6S-2F-Y



### G6S-2G, G6SU-2G, G6SK-2G, G6S-2G-Y



## Precautions

- Use a DC power supply with 5% or less ripple factor to operate the coil.
- Do not use the G6S where subject to strong external magnetic fields.
- Do not use the G6S where subject to magnetic particles or excessive amounts of dust.
- Do not reverse the polarity of the coil (+, -).
- Latching types are delivered in the reset position. We recommend that a reset voltage be applied in advance to start operation.
- Do not drop the G6S or otherwise subject it to excessive shock.
- Remove the relay from the packing immediately prior to usage.

## ■ Precautions

### Long-term Continuously ON Contacts

Using the Relay in a circuit where the Relay will be ON continuously for long periods (without switching) can lead to unstable contacts because the heat generated by the coil itself will affect the insulation, causing a film to develop on the contact surfaces. We recommend using a latching relay (magnetic-holding relay) in this kind of circuit. If a single-side stable model must be used in this kind of circuit, we recommend using a fail-safe circuit design that provides protection against contact failure or coil burnout.

### Relay Handling

Use the Relay as soon as possible after opening the moisture-proof package. If the Relay is left for a long time after opening the moisture-proof package, the appearance may suffer and seal failure may occur after the solder mounting process. To store the

Relay after opening the moisture-proof package, place it into the original package and sealed the package with adhesive tape.  
 When washing the product after soldering the Relay to a PCB, use a water-based solvent or alcohol-based solvent, and keep the solvent temperature to less than 40°C. Do not put the Relay in a cold cleaning bath immediately after soldering.

### G6S (K) (-U) -2 Soldering


Soldering temperature: Approx. 250°C (At 260°C if the DWS method is used.)

Soldering time: Approx. 5 s max. (Approx. 2 s for the first time and approx. 3 s for the second time if the DWS method is used.)

Be sure to adjust the level of the molten solder so that the solder will not overflow onto the PCB.

### Claw Securing Force During Automatic Mounting

During automatic insertion of Relays, be sure to set the securing force of each claw to the following so that the Relay's characteristics will be maintained.



Dimension A: 1.96 N max.  
 Dimension B: 4.90 N max.  
 Dimension C: 1.96 N max.