

Note: This datasheet may be out of date

Please download the latest datasheet of CFULB455KG1A-B0 from the official website of Murata Manufacturing

Co., Ltd.

https://www.murata.com/en-us/products/productdetail?partno=CFULB455KG1A-B0

CFULB455KG1A-B0










Appearance & Shape







Features

CFULB series ceramic filters are miniature, highperformance ceramic filters composed of piezoelectric elements connected in a ladder form. These filters, only 6.3mm high, are 65% the volume of conventional types. They are well suited for miniaturizing various kinds of communications equipment, pocket pagers, car radios, cordless telephones and mobile telephones.

Features

- 1. Miniature and high selectivity
- 2. Avariety of bandwidths are available
- 3. Operating temperature range: -20 to +80 (degrees C), Storage temperature range: -40 to +85 (degrees C)



Other Usage

Communication Equipment



Packaging Information

Packaging	Specifications	Minimum Order Quantity
-B0	Bulk	250

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated : 2019/12/17

Note: This datasheet may be out of date

Please download the latest datasheet of CFULB455KG1A-B0 from the official website of Murata Manufacturing

 $\begin{tabular}{ll} \hline $Co., Ltd. \\ \hline https://www.murata.com/en-us/products/productdetail?partno=CFULB455KG1A-B0 \\ \hline \end{tabular}$

CFULB455KG1A-B0



Operating Temperature Range	-20°C to 80°C	
Shape	Lead	
Elements	4	
Center Frequency	455.0kHz	
Center Frequency Tolerance	±1kHz	
Nominal Center Value	No	
6dB Bandwidth	fn±4.5kHzmin.	
Stop Bandwidth	10.0kHz	
Area of Stop Bandwidth	[within 40dB]	
Stop Band Attenuation	25dB[within fn±100kHz]	
Insertion Loss	6.0dB[at minimum loss point]	
Ripple	1.5dB[within fn±3kHz]	
Input/Output Impedance	2000Ω	

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/


Last updated :2019/12/17


Note: This datasheet may be out of date $\underline{ \text{Please download the latest datasheet of CFULB455KG1A-B0 from the official website of Murata Manufacturing} \\$ Co., Ltd.

https://www.murata.com/en-us/products/productdetail?partno=CFULB455KG1A-B0

CFULB455KG1A-B0








Frequency Characteristics

Spurious Response



Rg+R1=R2=Input/Output Impedance

Measurement Circuit

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/