



Part Number : 508029001

Series Number : 50802

Product Category : Crimp Terminals

Product Description : 2.50mm Pitch Mini-Latch Crimp Terminal, Female, Brass, Reel


Status : New Business Not Supported

Packaging Alternative : 508029101 (Bag)

Documents & Resources

Product Environment Compliance

Compliance

GADSL/IMDS	Compliant with Exemption 44
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	New Business Not Supported
Category	Crimp Terminals
Series	50802

Description	2.50mm Pitch Mini-Latch Crimp Terminal, Female, Brass, Reel
Application	Signal, Wire-to-Board, Wire-to-Wire
Product Family	Mini-Latch Wire-to-Board / Wire-to-Wire Connector System
Product Name	Mini-Latch
UPC	800753370593

Electrical

Current - Maximum per Contact	3.0A
-------------------------------	------

Physical

Durability (mating cycles max)	30
Gender	Female
Material - Metal	Brass
Material - Plating Mating	Tin
Material - Plating Termination	Tin
Net Weight	56.000/mg
Packaging Type	Reel
Plating min - Mating	0.889µm
Plating min - Termination	0.889µm
Termination Interface Style	Crimp or Compression
Wire Insulation Diameter	1.15-1.90mm
Wire Size (AWG)	22, 24, 26, 28
Wire Size mm ²	N/A

Application Tooling

Global

Description	Part Number
Extraction and Activation Tool	<u>638132700</u>
Hand Crimp Tool for 2.50mm Pitch SPOX Crimp Terminal, 22-28 AWG	<u>638281900</u>
FineAdjust Applicator for Wire-to-Board and Wire-to-Wire Terminal, 22-28 AWG Wire	<u>639004600</u>
T2 Terminator Tooling Die	<u>639104600</u>

Application Tooling

Japan

Description	Part Number
S-1 Applicator for Mini-Latch Terminals, 22-28 AWG	<u>2030913700</u>