

Features

- Low operating voltage: 3.6V
- Ultra low capacitance: 0.4pF (Typ)
- Ultra low leakage: nA level
- Low clamping voltage
- -IEC 61000-4-2 (ESD) immunity test
Air discharge: $\pm 20\text{kV}$
Contact discharge: $\pm 20\text{kV}$
- -IEC61000-4-4 (EFT) 40A (5/50ns)
- -IEC61000-4-5 (Lightning) 3A (8/20 μs)
- 2-pin leadless package
- These are Pb-Free Devices
- Response Time is Typically < 1 ns


Mechanical Characteristics

- Package: DFN0603-2(0201)
- Lead Finish: Matte Tin
- Case Material: "Green" Molding Compound
- Terminal Connections: See Diagram Below
- -IEC 61000-4-2 (ESD) immunity test

Applications

- Cellular Handsets and Accessories
- Personal Digital Assistants
- Notebooks and Handhelds
- Portable Instrumentation
- Power and data line

Dimensions and Pin Configuration



TPD1E04U04DPLR-TP

1-Line Uni-directional ESD DIODE


WWW.TECHPUBLIC.COM

Absolute Maximum Ratings (Tamb=25°C unless otherwise specified)

Parameter	Symbol	Value	Unit
Peak Pulse Current (8/20μs)	I _{pp}	3	A
ESD per IEC 61000-4-2 (Air)	VESD	±20	KV
ESD per IEC 61000-4-2 (Contact)		±20	
Operating Temperature Range	T _J	-40 to +125	°C
Storage Temperature Range	T _{stg}	-55 to +150	°C

Electrical Characteristics (TA=25°C unless otherwise specified)

Parameter	Symbol	Min	Typ	Max	Unit	Test Condition
Reverse Working Voltage	VRWM	--	--	3.6	V	Pin 1 to Pin 2
Breakdown Voltage	VBR	--	6.5	--	V	IT= 1mA, Pin 1 to Pin 2
Reverse Leakage Current	IR	--	--	50	nA	VRWM=3.3V, Pin 1 to Pin 2
Trigger voltage	V _{TRIG}	--	7.2	--	V	TLP, from Pin 1 to Pin 2
Reverse clamping Voltage (from Pin 1 to Pin 2)	V _{CL}	--	8	--	V	TLP, /PP = 16 A
		--	11	--	V	TLP, /PP = 30 A
Forward clamping voltage (from Pin 1 to Pin 2)	V _{FC}	--	6	--	V	TLP, /PP = 16 A
		--	9	--	V	TLP, /PP = 30 A
Dynamic resistance	R _{DYN}	--	0.19	--	Ω	TLP, Pin 1 to Pin 2
		--	0.23	--	Ω	TLP, Pin 2 to Pin 1
Junction Capacitance	C _J	--	0.4	0.6	pF	VR = 0V, f = 1MHz~1GHz



Characteristic Curves

Fig1. 8/20 μ s Pulse Waveform




Fig2. ESD Pulse Waveform (according to IEC 61000-4-2)






Fig3. Power Derating Curve




Package Outline & Dimensions

DFN0603-2 (0201)



SYM	DIMENSIONS		
	MILLIMETERS		
	MIN	NOM	MAX
A	0.230	0.300	0.330
A1	0.000	0.020	0.050
b	0.215	0.245	0.275
c	0.120	0.150	0.180
D	0.550	0.600	0.650
e	0.355 BSC		
E	0.250	0.300	0.350
L	0.160	0.190	0.220
h	0.079 BSC		

Suggested Land Pattern



SYM	DIMENSIONS	
	MILLIMETERS	INCHES
X	0.30	0.012
Y1	0.25	0.010
Y2	0.15	0.006
Y3	0.40	0.016
Z	0.65	0.026