



### Catalog No. CI12-AS2

**Description:** CONNECTOR INTERFACE AMP SUPERSEAL 2

**UPC No** 5020963021725

**Home > Cable Protection Systems > Harnessflex > Electrical connector assembly**

Hinged Connector Interface Fitting, Straight, 2-Way AS-AMP Superseal Connector to Conduit, Conduit Size NC12/NW10, Operating Temperature -40 to 120 Degrees Celsius, RoHS Compliant, IP40 Rating, Very High UV Protection, Polyamide (Nylon), Black

### Descriptors

|                  |                                                            |
|------------------|------------------------------------------------------------|
| Category         | Electrical connector assembly                              |
| Type             | Hinged AS-AMP Superseal Connector to Conduit               |
| Special Features | High Pull-Off Strength                                     |
| Application      | Provide Connection Between Connector Interface and Conduit |

### Specifications

|                          |                            |
|--------------------------|----------------------------|
| Connection               | Straight, 2-way connection |
| Material                 | Polyamide/Nylon            |
| Color                    | Black                      |
| Insulation               | IP40                       |
| Temperature Rating       | -40 to 120 C               |
| Environmental Conditions | Very High UV Protection    |

### Classifications

|            |                |
|------------|----------------|
| Brand Name | Harnessflex    |
| Standard   | RoHS Compliant |

### Dimensions

|      |                        |
|------|------------------------|
| Size | Conduit Size NC12/NW10 |
|------|------------------------|

### Compliance and Certifications

|            |                     |
|------------|---------------------|
| RoHS       | RoHS3 Compliant     |
| REACH SVHC | REACH 223 Compliant |