

https://www.phoenixcontact.com/us/products/1415782



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



HEAVYPORT B24 panel mounting base, with single locking latch, with plastic protective cover, with stainless steel front plate connections, 2x 120 V AC outlet

Your advantages

• Good shielding in the event of electromagnetic interference

Commercial data

Item number	1415782
Packing unit	1 pc
Sales key	BF69
Product key	BF7EGX
GTIN	4055626805832
Weight per piece (including packing)	22.22 g
Weight per piece (excluding packing)	22.22 g
Country of origin	US



https://www.phoenixcontact.com/us/products/1415782



Technical data

Product properties

Product type	Stackable housing set
Housing type	Panel mounting base
Application	Standard
Туре	B24
Protective cover	yes

Electrical properties

Rated voltage (III/3)	max. 125 V AC ()
	Requires slip-on sleeve: Item No. 3240541 or 3240536
Rated current	15 A ()

Connection data

Tightening torque	1.5 2 Nm

Dimensions

Dimensional drawing	64,5 130 140,5 53
Width	53 mm
Height	30.5 mm
Length	140.5 mm
Installation dimensions	
Width of the assembly cutout	35 mm

113 mm

Material specifications

Length of the assembly cutout

Seal material	NBR, conductive
	NBR, conductive
Housing material	Die-cast aluminum, salt water resistant
Housing surface material	uncoated
Material, protective cover	PA
Locking latch material	Polyamide

Connector

Contact insert design	with 2x 120 V AC outlet Terminal 6.35 mm (0.250 in.)
-----------------------	--

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP66
----------------------	------



https://www.phoenixcontact.com/us/products/1415782



	IP67
Impact strength	IK08
Ambient temperature (operation)	-40 °C 125 °C (Housing)

1415782


https://www.phoenixcontact.com/us/products/1415782




Drawings

Dimensional drawing 130 113 113 Ø4,5

Mounting cutout





Dimensional drawing



https://www.phoenixcontact.com/us/products/1415782



Classifications

ECLASS

ECLASS-11.0	27440101
ECLASS-12.0	27440113
ECLASS-13.0	27440113



https://www.phoenixcontact.com/us/products/1415782



Environmental product compliance

China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%



https://www.phoenixcontact.com/us/products/1415782



Accessories

C-SCFFI 2,5/4,8X0,5 - Connector

3240539

https://www.phoenixcontact.com/us/products/3240539



Slip-on sleeve, fully isolated, blue, 1.5 ... 2.5 mm², for plug 4.8 x 0.5 mm

C-SCFFI 1,5/4,8X0,5 - Connector

3240536

https://www.phoenixcontact.com/us/products/3240536



Slip-on sleeve, fully isolated, red, 0.5 ... 1.5 mm², for plug 4.8 x 0.5 mm

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com