

### **CHAMP**

TE Internal #: 6339447-9

Receptacle, Cable-to-Board, 50 Position, 2.16 mm [.085 in]

Centerline, 2 Row, Rectangular, Standard Profile, Right Angle, PCB

D-Sub Connectors

View on TE.com >



Connectors > D-Shaped Connectors > D-Sub Connectors > PCB D-Sub Connectors > D-Sub Shielded Receptacle Assembly: Right Angle, 2.16mm



Connector & Housing Type: Receptacle

Connector System: Cable-to-Board

Number of Positions: 50

Centerline (Pitch): 2.16 mm [ .085 in ]

Number of Rows: 2

All D-Sub Shielded Receptacle Assembly: Right Angle, 2.16mm (20)

### **Features**

## **Product Type Features**

Connector & Housing Type	Receptacle
Connector System	Cable-to-Board
Connector & Contact Terminates To	Printed Circuit Board

## **Configuration Features**

Number of Positions	50
Number of Rows	2
PCB Mount Orientation	Right Angle

## **Body Features**

Assembly Process Feature Material	Carbon Steel
Shield Plating Finish	Bright
Shield Plating Material	Nickel
Shield Material	Copper-Zinc Alloy
Connector Profile	Standard

### **Contact Features**

Contact Options	Installed
	30 μin
Contact Mating Area Plating Material	Gold



PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Copper Alloy
Contact Shape & Form	Rectangular
Contact Current Rating (Max)	3.5 A
Termination Features	
Rectangular Termination Post & Tail Thickness	.25 mm[.01 in]
Rectangular Termination Post & Tail Width	.5 mm[.019 in]
Termination Post & Tail Length	3.18 mm[.125 in]
Termination Method to PCB	Through Hole - Solder
Mechanical Attachment	
Assembly Process Feature Plating Material	Tin
PCB Mount Retention	With
PCB Mount Retention Type	Boardlock
Mating Retention	With
Mating Retention Type	4-40 Tapped Holes
Connector Mounting Type	Board Mount
Housing Features	
Housing Material	Polyester GF
Centerline (Pitch)	2.16 mm[.085 in]
Dimensions	
	.062 in
Row-to-Row Spacing	4.3 mm[.169 in]
Usage Conditions	
Operating Temperature Range	-40 - 105 °C[-40 - 221 °F]
Operation/Application	
Shielded	Yes
Circuit Application	Signal
Packaging Features	
Packaging Quantity	40
Packaging Method	Package

## **Product Compliance**



#### For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JAN 2021 (211) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach


## Compatible Parts



# Customers Also Bought

Receptacle, Cable-to-Board, 50 Position, 2.16 mm [.085 in] Centerline, 2 Row, Rectangular, Standard Profile, Right Angle, PCB D-Sub Connectors






TE Part #2180324-2 zSFP+ STACKED 2X4 RECEPTACLE ASSEMBLY



TE Part #1011-056-0305 SEAL RET, 3P, GRY, DTM



TE Part #2-552001-1 ASSY, RCPT, 50 POS, B SLOT



TE Part #1888247-2 20 POS SMT CONN, SFP/SFP+, 15A



TE Part #2007178-1 SFP+ 1x4 Cage Assembly, Light



TE Part #2-2013310-1 EMBOSS TAPE DDR3 204P 9.2H STD



TE Part #2289129-3
ZQSFP+ CAGE& CONN 2X2, EMI
SPRING, 4 LP

TE Part #1010-044-0306 SEAL, INTF, 3P, RED-ORG, DTM

TE Part #2199155-5 DDR4 DIMM 288 PIN SMT TYPE

TE Part #2380138-1 SFP+ 1X1 CAGE ASSEMBLY, TAIL, LIGHT PIPE

## **Documents**

**Product Drawings** 

RCPT ASSY,LP,SHLD,RA50,ILL,RVS

English

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_6339447-9\_B.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_6339447-9\_B.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_6339447-9\_B.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

**Product Specifications** 

Receptacle, Cable-to-Board, 50 Position, 2.16 mm [.085 in] Centerline, 2 Row, Rectangular, Standard Profile, Right Angle, PCB D-Sub Connectors



**Application Specification** 

English