### STRATO-THERM DIAMOND GRIP

TE Internal #: 1-321897-5

Closed Ring Tongue Terminal, 22 – 16 AWG, #8 / M5 Stud Size, 5.2 mm [.205 in] Stud Diameter, Closed Barrel, Straight, STRATO-


THERM DIAMOND GRIP

View on TE.com >



Terminals & Splices > Ring Terminals











Ring Terminal Product Type: Closed Ring Tongue Terminal

Wire Size: **509 – 3260 CMA** 

Stud Size: #8, M5

### **Features**

#### **Product Type Features**

Product Type Features	
Ring Terminal Product Type	Closed Ring Tongue Terminal
Stud Size	#8, M5
Sealable	No
Wire Insulation Support Retention Type	Insulation Support
Configuration Features	
Number of Holes	1
Contact Features	
Barrel Type	Closed
Terminal Orientation	Straight
Terminal Plating Material	Unplated
Mechanical Attachment	
Wire Insulation Support	With
Dimensions	
Wire Size	509 – 3260 CMA

5.2 mm[.205 in]

Stud Diameter



Tongue Thickness	.79 mm[.031 in]
Product Length	20.22 mm[.796 in]
Compatible Insulation Diameter (Max)	3.56 mm[.14 in]
Compatible Insulation Diameter Range	2.67 – 3.56 mm[.105 – .14 in]
Usage Conditions	
Insulation Option	Uninsulated
Operating Temperature Range	649 °C[1200 °F]
Operation/Application	
Compatible With Wire Base Material	Nickel
Industry Standards	
Government Qualified Terminal	No
Packaging Features	
Packaging Quantity	500

Loose Piece

# **Product Compliance**

Packaging Method

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits



as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach


# Compatible Parts






# Also in the Series | STRATO-THERM DIAMOND GRIP







# Customers Also Bought





















## **Documents**

### **Product Drawings**

DG 22-16 HT ALUMEL R M5

English

### **CAD Files**

**Customer View Model** 

ENG\_CVM\_CVM\_1-321897-5\_U.2d\_dxf.zip

English

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_1-321897-5\_U.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1-321897-5\_U.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.