



Part Number : 1200790141

Series Number : 120079

Product Category : Circular Industrial Cordsets

Product Description : Ultra-Lock (M12) Single-Ended Cordset, 4 Poles, Male (Straight) to Pigtail, 22 AWG, TPE Cable, 6.0m (19.68') Length

Status : Active

Engineering Number : W04006K05M060


Documents & Resources

Drawings

Drawing 1200790141_sd.pdf

Product Environment Compliance

Compliance

| | |
|--------------------|---|
| GADSL/IMDS | Not Relevant |
| China RoHS |  |
| EU ELV | Not Relevant |
| Low-Halogen Status | Not Low-Halogen per IEC 61249-2-21 |
| REACH SVHC | Contains Lead per D(2024)4144-DC (27 June 2024) |
| EU RoHS | Compliant with Exemption 6(c) per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| | |
|----------------|---|
| Status | Active |
| Category | Circular Industrial Cordsets |
| Series | 120079 |
| Description | Ultra-Lock (M12) Single-Ended Cordset, 4 Poles, Male (Straight) to Pigtail, 22 AWG, TPE Cable, 6.0m (19.68') Length |
| IP Rating | IP69K |
| Product Family | Brad Ultra-Lock Connection System |
| Product Name | Ultra-Lock (M12) |
| Protocol | EtherNet |
| Region | America |
| Type | Single Ended |
| UPC | 78678885015 |

Agency

| | |
|-----|--------|
| CSA | LR6837 |
|-----|--------|

Electrical

| | |
|-------------------------------|------------|
| Current - Maximum per Contact | 4.0A |
| Voltage - Maximum | 250V AC/DC |

Physical

| | |
|-------------------------|------------------|
| Cable Diameter | 5.30mm (.209") |
| Cable Length | 6.0m (19.68') |
| Color - Cable Jacket | Yellow |
| Connector End A | Ultra-Lock (M12) |
| Connector End B | Pigtail |
| Coupling Style | Push to Lock |
| Gender | Male-Pigtail |
| Keyway | Single |
| LED Indicator | No |
| Material - Cable Jacket | TPE |

| | |
|-------------------------------|-------------------------|
| Material - Connector Body | Thermoplastic Elastomer |
| Material - Contact | Copper Alloy |
| Material - Coupling Nut | Nickel-plated Brass |
| Material - O-Ring | Fluoro-elastomer |
| Material - Plating Mating | Gold |
| Net Weight | 1.000/g |
| Orientation | Straight to Pigtail |
| Poles | 4 |
| Temperature Range - Operating | -20° to +90°C |
| Wire/Cable Type | PLTC-ER |
| Wire Size (AWG) | 22 |