

[Home](#) | [Sign In](#) | [Site Map](#) | [Contact Us](#)

Cannon VEAM BIW

SEARCH [Home](#) > [Search Tools](#) > [Part Number](#)

Part Number Search

You Searched For:

Note: Data provided here are offered in good faith and are as reliable and accurate as possible. However, they do not form part of any contract of supply or purchase unless specifically confirmed in writing by an authorized representative of ITT. All information and images shown are the property of ITT ICS and are not to be reproduced in any form without direct authorization from ITT ICS. ITT ICS strongly recommends that you contact your local ITT Sales Office for confirmation of all the details you obtain through these Web pages. Please be aware that data may change at any time and without notice. For a listing of Sales Offices, local sales support, and authorized distributors please use the "Global Sales Locator" located either to the right of this data or at the top of every page.

[Sales Support](#)[Product Overview](#)[Stock Check](#)[View 2D Drawing](#)

The requested part number is currently unsupported in our on-line configuration system. (d)

Product Datasheet

Thread	Connector with threaded coupling
Shell Style	Plug, straight
Endbell Style	Endbell with clamp and bushing
Gender	Pin
Shell Size	20
Contact Arrangement	20-29
Number of contacts	17 contacts size 16
Contact Type	Solder Cup
Contact Plating	Gold 0,5 µ
Shielding	no
Contact Rating at +20 °C (68 °F) (Size 15/15S/16/16S)	22 A
Contact Resistance (Size 15/15S/16/16S)	6 mΩ
Operating Voltage	In case of voltages greater than 50V the connector must be used in accordance with DIN VDE part 410, IEC 60364-4-41. Acc. To VG95319, part 2, test no. 5.12 and VG95210, part 32, test conditions B, standard insulator material > 1000 MΩ
Insulator Resistance	1600 Vrms
Test Voltage	1,1 mm
Air and Creepage Paths (Min)	Standard insulator material -55°/+125°C (-67/257°F)
Ambient Temperature	IP67 acc. to DIN 40 050 (1 bar pressure after 12 hrs) 48 hours salt spray resistant
Safety Provisions	500 min
Salt Spray Resistance	1,0 N
Mating Cycles	For infos on Gage please see catalog VG95234, part 1
Sep. Force per Contact (Size 15/15S/16/16S)	Closing: 9 Nm max / Opening: 0,7 Nm min
Gage	35 N
Coupling Torque	Aluminium alloy
Contact Retention (Size 15/15S/16/16S)	Black Zinc Cobalt (conductive)
Shell Material	Neoprene
Shell Plating	Copper alloy
Insulator and Gromet Material	See assembly instruction
Contact Material	See assembly instruction
Hamessing Info: Contact Cross-Section	
Hamessing Info: Insulator Diameter	
Wire Stripping (Size 15/15S/16/16S)	6,2 mm
General Info	All tests in accordance with VG95319 and/or if applicable with VG95210

[Home](#) | [About ITT](#) | [Products](#) | [Design Center](#) | [Literature](#) | [News & Events](#) | [Search Tools](#) | [Global Sales Support](#)[Channel Partners Sign-In](#)[Legal Disclaimer](#) | [Privacy Policy](#) | [Terms & Conditions](#) |  [Provide Website Feedback](#)

© 2012 ITT Corporation. All rights reserved.