

Search Results

- Evaluate
- FAQ's

- Press Releases

-Stainless St..

- Product Bulletins

- PDFStainless St..
- Design a Solution
- Part Drawings

- PDFMLT, Heavy S..
- How to Buy
- Bill of Material

- Favorite Products List

- Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove)

Search Tips

 Text Search: 'MLTFC2HLP316WH'

Your search criteria matched only one product, shown below

MLTFC2HLP316WH



- Polyester coating available in six color options provides visual indication for easy identification in color-coding applications (heavy cross section only)
 - Self-locking head design speeds installation and locks into place at any length along the tie body
 - Polyester coating provides additional edge protection and prevents corrosion between dissimilar metals
 - AISI 316 stainless steel for the most corrosive environments
 - Available in standard, heavy, extra-heavy and super-heavy cross sections
 - UV resistant, low smoke, halogen -free material
 - Temperature tolerance -40°F (-40°C) to 302°F (150°C)
- Part thickness is base material less coating.

 Part Number	MLTFC2HLP316WH
 RoHS Compliancy Status	Compliant
 Part Description	Polyester coated stainless steel tie, AISI 316, heavy, 7.9" length.
 Product Type	Stainless Steel Cable Tie
 Material	Stainless Steel Type 316 (V4A)
 Color	White
 Length (In.)	7.9
 Length (mm)	201
 Width (In.)	0.31
 Width (mm)	7.9
 Max. Bundle Diameter (In.)	2.0
 Max. Bundle Diameter (mm)	51
 Min. Bundle Diameter (In.)	0.50
 Min. Bundle Diameter (mm)	12.7
 Min. Loop Tensile Strength (Lbs.)	250
 Min. Loop Tensile Strength (N)	1112
 Pricing Description	MLT Tie, 316 SS, Fully Coated, Heavy, 7.9" (201mm), .010" (.25mm) thk, White
 Temperature Range	-40°C– 150°C
 Thickness (In.)	0.010
 Thickness (mm)	0.25
 Tool	GS4MT, ST2MT, HTMT, PPTMT, PBTMT
 Min. Order UOM	PC
 Min. Order Qty.	50
 BOM Qty. (# of Pkgs.)	0
 Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.