T4081112003-000 ACTIVE

M8 Connector

TE Internal #: T4081112003-000

Cable-to-Cable, 3 Position, Sealable, Wire & Cable, Signal, Cable Mount (Free-Hanging), Reverse Gender, M8 Connector, Standard

Circular Connectors

View on TE.com >



Connectors > Circular Connectors > Standard Circular Connectors











Connector System: Cable-to-Cable

Connector Mounting Type: Cable Mount (Free-Hanging)

Number of Positions: 3

Sealable: Yes

Connector & Contact Terminates To: Wire & Cable

Features

Product Type Features

Product Type	Connector Assembly
Accessory Color	Black
Assembly Requirement	Factory Assembled
Assembly Type	Electrical Connector
Circular Connector Shell Type	All Plastic
Connector Product Type	Connector Assembly
Connector System	Cable-to-Cable
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable
Circular Connector Type	Plug
Shell Type	Plastic
Configuration Features	
Keying & Polarized Position Locations	A
Factory Installed Backshell	No



Keying	A
Number of Positions	3
Number of Power Positions	0
Number of Signal Positions	3
Contacts Preloaded	Yes
Electrical Characteristics	
Operating Voltage	60 VAC
Body Features	
Peripheral Seal Material	Silicone
Environmental Protection	IP67
O-Ring Material	Silicone
Environmental Protection Type	Sealed
Shell Plating Material	Unplated
Shell Base Material	Plastic
Circular Connector Insulation Material Type	Polyamide 66 GF25
Hermetically Sealed	Yes
Contact Features	
Contact Features Contact Current Rating (Max)	4 A
	4 A Yes
Contact Current Rating (Max)	
Contact Current Rating (Max) Reverse Gender	Yes
Contact Current Rating (Max) Reverse Gender Circular Connector Contact Type	Yes
Contact Current Rating (Max) Reverse Gender Circular Connector Contact Type Mechanical Attachment	Yes Pin
Contact Current Rating (Max) Reverse Gender Circular Connector Contact Type Mechanical Attachment Connector Mounting Type	Yes Pin Cable Mount (Free-Hanging)
Contact Current Rating (Max) Reverse Gender Circular Connector Contact Type Mechanical Attachment Connector Mounting Type Polarization Code	Yes Pin Cable Mount (Free-Hanging) A
Contact Current Rating (Max) Reverse Gender Circular Connector Contact Type Mechanical Attachment Connector Mounting Type Polarization Code Mating Alignment Type	Yes Pin Cable Mount (Free-Hanging) A
Contact Current Rating (Max) Reverse Gender Circular Connector Contact Type Mechanical Attachment Connector Mounting Type Polarization Code Mating Alignment Type Usage Conditions	Yes Pin Cable Mount (Free-Hanging) A Keyed
Contact Current Rating (Max) Reverse Gender Circular Connector Contact Type Mechanical Attachment Connector Mounting Type Polarization Code Mating Alignment Type Usage Conditions IP Dust Sealing Level	Yes Pin Cable Mount (Free-Hanging) A Keyed
Contact Current Rating (Max) Reverse Gender Circular Connector Contact Type Mechanical Attachment Connector Mounting Type Polarization Code Mating Alignment Type Usage Conditions IP Dust Sealing Level IP Water Sealing Level	Yes Pin Cable Mount (Free-Hanging) A Keyed 6 IP67
Contact Current Rating (Max) Reverse Gender Circular Connector Contact Type Mechanical Attachment Connector Mounting Type Polarization Code Mating Alignment Type Usage Conditions IP Dust Sealing Level IP Water Sealing Level Operating Temperature Range	Yes Pin Cable Mount (Free-Hanging) A Keyed 6 IP67
Contact Current Rating (Max) Reverse Gender Circular Connector Contact Type Mechanical Attachment Connector Mounting Type Polarization Code Mating Alignment Type Usage Conditions IP Dust Sealing Level IP Water Sealing Level Operating Temperature Range Operation/Application	Yes Pin Cable Mount (Free-Hanging) A Keyed 6 IP67 -40 – 85 °C[-40 – 185 °F]
Contact Current Rating (Max) Reverse Gender Circular Connector Contact Type Mechanical Attachment Connector Mounting Type Polarization Code Mating Alignment Type Usage Conditions IP Dust Sealing Level IP Water Sealing Level Operating Temperature Range Operation/Application Durability Rating	Yes Pin Cable Mount (Free-Hanging) A Keyed 6 IP67 -40 – 85 °C[-40 – 185 °F] 100 Cycles



Industry Standards

UL Flammability Rating	UL 94HB
Packaging Features	
Packaging Quantity	1

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JAN 2024 (240) SVHC > Threshold: Pb (4% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





Also in the Series | M8 Connector









Connector Hardware(4)

M8/M12 Cable Assemblies(147)

Standard Circular Connectors(106)

Customers Also Bought









TE Part #T4052118004-001 RPC-M8-4MS-0.5-M12-4FR-PVC



TE Part #T4062123003-001 RPC-M8-3MS-0.5SH-M8-3FS-PUR




TE Part #284506-6 6 POS TERMI-BLOK PLUG STACK 3,



TE Part #284506-8 8 POS TERMI-BLOK PLUG STACK 3,



TE Part #60888-1 058 PIN REC 26-22 .010PTPPHBZ



TE Part #9800944001 RNF-100-1/2-0-FSP



TE Part #5052844025 RNF-100-3/64-0-SP



TE Part #890036-000 S1009-KIT-A

TE Part #5-1617002-2 B07B112CC1-0301 = RELAY.



Documents

Product Drawings

M8 Y DISTRIBUTOR MALE 3POS

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_T4081112003-000_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_T4081112003-000_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_T4081112003-000_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

M8 / M12 Connector System Catalog

English

Product Specifications

Application Specification

English

Application Specification

English

Agency Approvals

UL

English