

Catalog No. CPO250-0-25

Description: HTSHK THIN WALL 1/4IN I.D. BLK 25FT

UPC No 786210851174

Home > Connectivity & Grounding > Shrink-Kon > Heat shrinkable tube

Thin-Wall Heat Shrinkable Tubing, Black Cross-Linked Polyolefin, 1/4 Inch, Shrink Ratio 2:1, Length 25-Foot Reel, Operating Temperature -55 to 135 Degrees Celsius, Non-Lined

Representative Image

Descriptors

Category	Heat shrinkable tube
Type	Thin-Wall Heat Shrinkable Tubing
Special Features	Flame-retardant, cross-linked polyolefin.

Specifications

Voltage Rating	600 V
Color	Black

Classifications

Brand Name	Shrink-Kon
------------	------------

Dimensions

Thickness	Thin
Length	25 ft

Compliance and Certifications

RoHS	RoHS3 Compliant
TSCA	TSCA Section 6(h) Compliant
POPs	POPs 28 Compliant

ETIM	EC000217 Shrink tubing
Type	Heat-shrink
Model	Thin-walled
Shrink rate	2:1
Inner diameter before heat-shrink	6.35 mm
Inner diameter before heat-shrink	0.25 inch
Inner diameter after heat-shrink	3.302 mm

ETIM	EC000217 Shrink tubing
Inner diameter after heat-shrink	0.13 inch
Nominal diameter inch	1/4 inch
Wall thickness after shrinking	0.508 mm
Wall thickness after shrinking	0.02 inch
Length	7.62 m
Length	25 ft
Operation temperature	-55-+135 °C
Operation temperature	-67-+275 °F
Colour	Black
Material	Polyolefin (PO-X)
Halogen free	N
With inner glue	N
Printable	N
UL approval	Y