



RAST

TE Internal #: 1534415-6


Wire-to-Board, 6 Position, 5 mm [.197 in] Centerline, Insulation

Displacement (IDC), 1 Row, Natural, PA 6, Standard Edge

Connectors

[View on TE.com >](#)

Connectors > PCB Connectors > Card Edge Connectors > Standard Edge Connectors



Connector System: **Wire-to-Board**

Number of Positions: **6**

Centerline (Pitch): **5 mm [.197 in]**

Termination Method to Wire & Cable: **Insulation Displacement (IDC)**

Number of Rows: **1**

Features

Product Type Features

Connector System	Wire-to-Board
Connector & Housing Type	Receptacle
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Card Entry Style	Side
Compatible With Wire & Cable Type	Discrete Wire
Number of Positions	6
Number of Rows	1
Connector Contact Load Condition	Fully Loaded
PCB Mount Orientation	Right Angle

Electrical Characteristics

Operating Voltage	250 VAC
-------------------	---------

Body Features

Primary Product Color	Natural
-----------------------	---------



Contact Features

Contact Retention Within Housing	With
Contact Type	Socket
Contact Mating Area Plating Material Thickness	3 – 6 µm[196.849 – 787.399 µin]
Contact Mating Area Plating Material	Tin
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Copper Nickel Silicon
Contact Current Rating (Max)	6 A

Termination Features

Termination Method to Wire & Cable	Insulation Displacement (IDC)
------------------------------------	-------------------------------

Mechanical Attachment

Mating Alignment Type	Keyed
Mating Retention	With
Mating Alignment	With
Contact Retention Type Within Housing	Locking Lance
PCB Mount Alignment	With
PCB Mount Retention	Without
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Housing Entry Configuration	One End Open
Centerline (Pitch)	5 mm[.197 in]
Housing Material	PA 6

Dimensions

Connector Height	7.3 mm[.287 in]
PCB Thickness (Recommended)	1.5 mm[.059 in]
Compatible Insulation Diameter Range	2.2 mm[.087 in]
Wire Size	.35 – .5 mm²

Usage Conditions

Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]
-----------------------------	----------------------------

Operation/Application

Circuit Application	Power
---------------------	-------



Industry Standards

Compatible With Agency/Standards Products	UL
UL Flammability Rating	UL 94V-2
Glow Wire Rating	GWT 750°C (Without Flame)

Packaging Features

Packaging Quantity	1232
Packaging Method	Tray

Product Compliance

For compliance documentation, visit the product page on TE.com>









EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



 TE Part # 1394918-6 DUOPLG5.0 BU-STE 6P	 TE Part # 2-1534415-2 DUOPL POW FEM CON2P	 TE Part # 1534415-3 DUOPL POW FEM CON3P	 TE Part # 1534415-2 DUOPL POW FEM CON2P
 TE Part # 1534415-4 DUOPL POW FEM CON4P	 TE Part # 1534415-5 DUOPL POW FEM CON5P	 TE Part # 1534415-7 DUOPL POW FEM CON7P	 TE Part # 1-1534415-3 DUOPL POW FEM CON3P
 TE Part # 1534415-8 DUOPL POW FEM CON8P	 TE Part # 1-1534415-2 DUOPL POW FEM CON2P	 TE Part # 2-1534415-3 DUOPL POW FEM CON3P	 TE Part # 3-1534415-2 DUOPL POW FEM CON2P
 TE Part # 4-1534415-3 DUOPL POW FEM CON 3P	 TE Part # 2388178-6 DUOPLUG POW CONN 6P GW-V0		


Customers Also Bought

 TE Part #9-1241961-2 STD TIM HOUSING MKII 2POS	 TE Part #3-1534796-5 AMP DUOPLUG MK2 CONNECTOR 5P	 TE Part #3-1534798-3 AMP DUOPLUG MK2 CONNECTOR 3P SELECTIVE	 TE Part #1534415-4 DUOPL POW FEM CON4P
---	---	--	---





TE Part #3-1534796-8
AMP DUOPLUG MK2 CONNECTOR 8P



TE Part #1-282044-1
AMP MONO-SHAPE P.C.B.CONN4P.G



TE Part #3-1534798-5
AMP DUOPLUG MK2 CONNECTOR 5P SELECTIVE

TE Part #1544114-3
CLIP DRAPEAU 6,35



TE Part #1544113-3
CLIP DRAPEAU 6,35

Documents

Product Drawings

DUOPL POW FEM CON6P

English

CAD Files

Customer View Model

ENG_CVM_CVM_1534415-6_D.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1534415-6_D.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1534415-6_D.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

RAST Connector System Catalog

English

Product Specifications

Application Specification

English

Agency Approvals

VDE Certificate

1534415-6

Wire-to-Board, 6 Position, 5 mm [.197 in] Centerline, Insulation Displacement (IDC), 1 Row, Natural, PA 6, Standard Edge Connectors



English

[VDE Certificate](#)

English