

N-channel Enhancement Mode Power MOSFET


Features

- $V_{DS} = 200\text{ V}$, $I_D = 8\text{ A}$
 $R_{DS(ON)} < 260\text{ m}\Omega$ @ $V_{GS} = 10\text{ V}$
 $R_{DS(ON)} < 300\text{ m}\Omega$ @ $V_{GS} = 4.5\text{ V}$

General Features

- Advanced Trench Technology
- Provide Excellent $R_{DS(ON)}$ and Low Gate Charge
- Lead Free and Green Available


100% UIS TESTED!
100% ΔV_{ds} TESTED!



TO-252-2L Top View



Pin Assignment



Schematic Diagram

Absolute Maximum Ratings ($T_C = 25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V_{DS}	200	
Gate-Source Voltage	V_{GS}	± 20	
Drain Current-Continuous	I_D	8	
Drain Current-Continuous ($T_C = 100^\circ\text{C}$)	$I_D(100^\circ\text{C})$	5	A
Pulsed Drain Current	I_{DM}	20	
Maximum Power Dissipation	P_D	55	
Operating Junction and Storage Temperature Range	T_J, T_{STG}	-55 To 150	$^\circ\text{C}$

Thermal Characteristic

Thermal Resistance, Junction-to-Case ^(Note 2)	$R_{\theta JC}$	2.3	$^\circ\text{C/W}$
--	-----------------	-----	--------------------

Electrical Characteristics ($T_C=25^{\circ}\text{C}$ unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Off Characteristics						
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} =0V I _D =250μA	200	215	-	V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =200V, V _{GS} =0V	-	-	1	μA
Gate-Body Leakage Current	I _{GSS}	V _{GS} =±20V, V _{DS} =0V	-	-	±100	nA
On Characteristics (Note 3)						
Gate Threshold Voltage	V _{GS(th)}	V _{DS} =V _{GS} , I _D =250μA	1		3.0	V
Drain-Source On-State Resistance	R _{DS(ON)}	V _{GS} =10V, I _D =4.5A	-	260		mΩ
Forward Transconductance	g _{FS}	V _{DS} =25V, I _D =4.5A	3	-	-	S
Dynamic Characteristics (Note4)						
Input Capacitance	C _{ISS}	V _{DS} =25V, V _{GS} =0V, F=1.0MHz		540		PF
Output Capacitance	C _{OSS}			90		PF
Reverse Transfer Capacitance	C _{rss}			35		PF
Switching Characteristics (Note 4)						
Turn-on Delay Time	t _{d(on)}	V _{DD} =100V, I _D =4.5A V _{GS} =10V, R _{GEN} =5Ω	-	6.4	-	nS
Turn-on Rise Time	t _r		-	11	-	nS
Turn-Off Delay Time	t _{d(off)}		-	20	-	nS
Turn-Off Fall Time	t _f		-	12	-	nS
Total Gate Charge	Q _g	V _{DS} =160V, I _D =4.5A, V _{GS} =10V	-	16	-	nC
Gate-Source Charge	Q _{gs}		-	3.4	-	nC
Gate-Drain Charge	Q _{gd}		-	5.1	-	nC
Drain-Source Diode Characteristics						
Diode Forward Voltage (Note 3)	V _{SD}	V _{GS} =0V, I _S =8A	-	-	1.2	V
Diode Forward Current (Note 2)	I _S		-	-	8	A

Notes:

1. Repetitive Rating: Pulse width limited by maximum junction temperature.
2. Surface Mounted on FR4 Board, $t \leq 10$ sec.
3. Pulse Test: Pulse Width $\leq 300\mu s$, Duty Cycle $\leq 2\%$.
4. Guaranteed by design, not subject to production

Typical Electrical and Thermal Characteristics (Curves)




Figure 1 Output Characteristics




Figure 4 $R_{DS(on)}$ -Junction Temperature




Figure 2 Transfer Characteristics




Figure 5 Gate Charge




Figure 3 $R_{DS(on)}$ - Drain Current




Figure 6 Source- Drain Diode Forward




Figure 7 Capacitance vs V_{ds}




Figure 9 BV_{dss} vs Junction Temperature




Figure 8 Safe Operation Area




Figure 10 $V_{GS(th)}$ vs Junction Temperature




Figure 11 Current De-rating




Figure 12 Normalized Maximum Transient Thermal Impedance