

**Product Description :** CLIK-Mate Plug Housing, 1.50mm Pitch, Dual Row, Positive Lock, 20 Part Number: 5031492000

Circuits, Natural Status: Active

Series Number: 503149

**Product Category:** Connector Housings

#### **Documents & Resources**

### **Drawings**

Drawing 5031492000\_sd.pdf

#### 3D Models and Design Files

2D Drawing DXF 5031492000.dxf

2D Drawing DXF (PDF) 5031492000.pdf

3D Model 5031492000\_stp.zip

### **Specifications**

Application Specification AS-503149-001-001.pdf Packaging Specification SPK-503149-001-001.pdf Product Specification 5031490000-PS-000.pdf Product Specification 5031491000-PS-000.pdf Product Specification 5031491001-PS-000.pdf Product Specification 5031491002-PS-000.pdf Product Specification 5031491003-PS-000.pdf Product Specification PS-505406-001-001.pdf

## **Product Environment Compliance**

### Compliance

GADSL/IMDS	Not Relevant
China RoHS	<b>©</b>
EU ELV	Not Relevant
Low-Halogen Status	Not Low-Halogen per IEC 61249-2- 21
REACH SVHC	Not Contained per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant per EU 2015/863

### Multiple Part Product Compliance Statements

- Eu RoHS

- REACH SVHC
- Low-Halogen

## Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

## EU RoHS Certificate of Compliance

## **Part Details**

### General

Status	Active
Category	Connector Housings
Series	503149
Description	CLIK-Mate Plug Housing, 1.50mm Pitch, Dual Row, Positive Lock, 20 Circuits, Natural
Application	Signal, Wire-to-Board
Product Family	CLIK-Mate Wire-to-Board Connectors
Product Name	CLIK-Mate
UPC	800756961699

## Agency

UL	E29179
----	--------

## **Physical**

Circuits (maximum)	20
Color - Resin	Natural
Gender	Plug
Glow-Wire Capable	No
Keying to Mating Part	None
Lock to Mating Part	Yes
Material - Resin	PBT
Number of Rows	2
Packaging Type	Bag

Panel Mount	No
Pitch - Mating Interface	1.50mm
Pitch - Termination Interface	1.50mm
Polarized to Mating Part	Yes
Stackable	No
Temperature Range - Operating	-40° to +105°C

## Mates With / Use With

# Mates with Part(s)

Description	Part Number
1.50mm Pitch CLIK-Mate Right- Angle Dual Row PCB Receptacles	213228
1.50mm Pitch CLIK-Mate Right- Angle Dual Row PCB Receptacles	503148
1.50mm Pitch CLIK-Mate Vertical Dual Row PCB Receptacles	213227
1.50mm Pitch CLIK-Mate Right- Angle Dual Row PCB Receptacles	503154

# Use with Part(s)

Description	Part Number
Pre-Crimped Lead CLIK-Mate 1.50mm Male-to-CLIK-Mate 1.50mm Male, Tin (Sn) Plating, 300.00mm Length, 24 AWG, Black	/content/molex/molex-dot- com/us/en/products/product-page- pdf.html/797581011.html
1.50mm Pitch CLIK-Mate Male Crimp Terminals	502579
1.50mm Pitch CLIK-Mate Male Crimp Terminals	503429
CLIK-Mate 1.50mm Pitch Male Crimp Terminals	213028
CLIK-Mate 1.50mm Pitch Male Crimp Terminals	213029
Pre-Crimped Lead Clik-Mate Male- to-Clik-Mate Male	<u>215710</u>
Pre-Crimped Lead Clik-Mate Male- to-Pigtail	<u>215711</u>